

ALGINE BACKLIGHT

SLI035059NW_PW



See
more

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 120 lm/W. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	40 W	Voltage	230 V
Luminous flux*	4800 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
Degree of protection (IP)	IP20		


Technical data

Code	SLI035059NW_PW
Power	40 W
Nominal current	173 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4800 lm (360°)
Luminous flux**	3800 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	295x1195x25 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC




Related documents



 User manual



 Declaration of Conformity



 Photometric file

