

PRODUCT DATASHEET

ST8PRO-HF 20 W/4000 K 1500 mm

SubstiTUBE T8 HF PRO | LED tubes for electronic high frequency control gears (ECG), shatterproof



Areas of application

- General illumination within ambient temperatures from -20...+45 °C
- Supermarkets and department stores
- Industry
- Offices, public buildings

Product benefits

- Quick, simple and safe replacement without rewiring
- Shatter protection thanks to special PET coating
- Also suitable for operation at low temperatures
- High luminous flux for sophisticated lighting tasks
- No bending thanks to glass technology

Product features

- T8 LED tube made of glass with G13 base
- Low flicker according to EU 2019/2020
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime: up to 60,000 h
- Compatible with many common electronic control gears (see also compatibility list)



TECHNICAL DATA

Electrical data

Nominal wattage	20 W
Construction wattage	20.00 W
Nominal voltage	40...70 V
Operating mode	Electronic control gear (ECG)
Nominal current	110 mA
Type of current	AC
Inrush current	22 A
Operating frequency	20...75 kHz
Mains frequency	20...75 kHz
Max. lamp no. on circuit break. 10 A (B)	55
Max. lamp no. on circuit break. 16 A (B)	90
Total harmonic distortion	< 20 %
Power factor λ	> 0.90

Photometrical data

Luminous flux	3100 lm
Luminous efficacy	155 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	83
Light color	840
Standard deviation of color matching	≤ 5 sdc _m

Light technical data

Beam angle	190 °
Warm-up time (60 %)	< 2.00 s
Starting time	< 0.5 s

Dimensions & Weight



Overall length	1513.10 mm
Diameter	27.80 mm
Tube diameter	25,5 mm
Maximum diameter	28 mm
Product weight	248.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	78 °C

Lifespan

Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

Additional product data

Base (standard designation)	G13
Mercury content	0.0 mg

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Energy efficiency class	D
Energy consumption	22.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	RL-T8 58 S 20W/
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Correlated colour temperature type	SINGLE_VALUE

Length	1513.10 mm
Height	27.80 mm
Width	27.80 mm
EPREL ID	519424

Safety advice

- Not suitable for operation with low-loss and conventional control gears and main voltage.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc max temperature on the product prior to installation.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008597200601	Sleeve 1	1,520 mm x 31 mm x 31 mm	277.00 g	1.46 dm ³
4008597600609	Shipping box 10	1,572 mm x 210 mm x 115 mm	3544.00 g	37.96 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.