



Description MINIATURE CIRCUIT BREAKER

Code MT 60

No. of poles 1P

No. modules 1

Rated current 25 A

Curve B

Rated voltage 230-400 V

|   |   |  |   |
|---|---|--|---|
| Standard                                    | EN 60898, EN 60947-2                          | Rated frequency (Hz)                   | 50/60 Hz                                      |
| Breaking capacity EN 60898 230V (Icn)       | 6000 A  | Breaking capacity EN 60898 (Ics)       | 1 x Icn                                       |
| Breaking capacity IEC/EN 60947-2 230V (Icu) | 10 kA   | Breaking capacity IEC/EN 60947-2 (Ics) | 75% Icu                                       |
| Insulation voltage                          | 500 V   | Rated impulse withstand voltage        | 4 kV  |
| Minimum operating voltage                   | 12V ac/dc                                     | Maximum operating voltage              | 440V AC / 220V DC                             |
| Electrical endurance                        | 10.000  | Mechanical endurance                   | 20.000  |
| Section rigid cable                         | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> | Section flexible cable                 | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> |
| Rated tightening torque                     | 2 Nm  | Operating temperature                  | -25 +60 °C                                    |
| Stocking temperature                        | -40 +70 °C                                    | Electrocod                             | 1411  |

### DIMENSIONAL



### STANDARDS/APPROVALS

