


Vision HP



- IP65 polycarbonate LED luminaire suitable for external hospitality and retail applications and ancillary areas
- Four conduit entry points
- Integral die-cast aluminium heatsink provides thermally managed high performance
- Dimmable, Photocell, MWS and Emergency options available
- Powered by Tridonic



Removable conduit entry cap for ease of installation

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
230V	50/60Hz	-10°C to 50°C	L70 36,000	Ra 80	6	110°	1	IP65	IK09

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	TRADE
AVILED/HP/GR	Cool White	31W	4000K	2426lm	78lm	£128.00

CODE (OPTIONS)	DESCRIPTION	TRADE
/PC	Electronic Photocell	+ £36.00
/M3	Emergency (14W only)	+ £90.00

CODE (OPTIONS)	DESCRIPTION	TRADE
/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00
/MWS	Integral Microwave Sensor	+ £60.00
/CF	Corridor Function	+ £37.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AVILED/GR/EYE	Eyelid Accessory - Graphite	£11.80

CODE (ACCESSORIES)	DESCRIPTION	TRADE
AVILED/GR/LVD	Louvered Accessory - Graphite	£10.85