

## SAG DCA P HR GA (767 101)

- Nominal voltages up to 45 kV / 50 Hz (three-phase systems)
- LED indication



Figure without obligation




Figure without obligation

| Type                              | SAG DCA P HR GA                                 |
|-----------------------------------|---|
| Part No.                          | 767 101   |
| Nominal voltage (U <sub>N</sub> ) | 1 ... 45 kV                                     |
| Frequency                         | 50 Hz   |
| Dimensions                        | 40 x 48 x 35 mm                                 |
| Plug spacing                      | 19 mm   |
| Indication threshold (HR system)  | 90 V  |
| Input impedance (HR system)       | 36 MOhms  |
| Standard                          | EN/IEC 61243-5 (DIN VDE 0682-415)               |
| Temperature range                 | -25 °C ... +55 °C                               |
| Degree of protection              | IP 66   |
| Type of device                    | Voltage indicator                               |
| Use                               | Can also be used as permanent voltage indicator |
| Indication                        | Visual  |
| Type of system                    | HR  |
| Self-testing element              | No  |
| Weight                            | 60 g  |
| Customs tariff number             | 90303320  |
| GTIN                              | 4013364069541                                   |
| PU                                | 1 Stk   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.