

Accessories / LED Bulb

LED Bulb E27 24VAC/DC RD



Part No.: 956.120.75



MECHANICAL DATA

| | |
|-----------------------|-------|
| Height | 65 mm |
| Diameter | 45 mm |
| Materials | PC |
| Weight with packaging | 34 g |
| Product weight | 26 g |

ELECTRICAL DATA

| | |
|-----------------------------|---------|
| Operating voltage | 24V |
| Operating voltage type | AC/DC |
| Operating voltage frequency | 50Hz |
| Operating voltage tolerance | +/- 10% |
| Rated operational voltage | 24 VDC |
| Rated operational current | 20 mA |
| Rated inrush current | 500 mA |

OPTICAL DATA

| | |
|----------------------|------------------|
| Light source | LED |
| Light colour | Red |
| Optical signal image | Permanent |
| Service life optical | 50,000 h maximum |
| Lamp fitting/socket | E27 |

APPROVAL DATA

| | |
|------------------------------|-----|
| Conforms with CE | Yes |
| Conforms with RoHS directive | Yes |
| WEEE | No |
| Conforms with ATEX-directive | No |
| Conforms with CCC | No |
| Conforms with FCC | No |
| Conforms with IC | No |
| EAC certificate available | No |
| Conforms with AS-I | No |
| ICAO Certification | No |
| Conforms with DNV | No |
| Conforms with RoHS CN | No |




For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.

Accessories / LED Bulb

LED Bulb E27 24VAC/DC RD

DRAWING



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.