

ALGINE BACKLIGHT

SLI035066CW_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 145 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.




Power	40 W	Voltage	230 V
Luminous flux*	5800 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
UGR	<19	Degree of protection (IP)	IP20

Technical data


Code	SLI035066CW_PW
Power	40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	5800 lm (360°)
Luminous flux**	4800 lm (360°)
Lamp efficacy	145 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

