

PRODUCT DATASHEET LED VALUE CLAS A 40 4.9 W/4000 K E27

LED VALUE CLASSIC A | LED lamps, classic bulb shape



Areas of application

- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Can be easily fitted instead of ordinary light bulbs

Product features

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering ($R_a \ge 80$) and color stability throughout the life of the lamp





TECHNICAL DATA

Electrical data

| Nominal wattage | 4.9 W |
|--|----------|
| Construction wattage | 4.90 W |
| Nominal voltage | 220240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Nominal current | 42 mA |
| Type of current | AC |
| Operating frequency | 5060 Hz |
| Mains frequency | 5060 Hz |
| Power factor λ | > 0.50 |


Photometrical data

| Luminous flux | 470 lm |
|---|------------|
| Nominal useful luminous flux 90° | 470 lm |
| Luminous efficacy | 95 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcm |
| Rated LLMF at 6,000 h | 0.80 |

Light technical data

| Beam angle | 200 ° |
|---------------------|---------|
| Warm-up time (60 %) | 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| Overall length | 95.00 mm |
|------------------|----------|
| Diameter | 55.00 mm |
| Maximum diameter | 55 mm |
| Product weight | 20.00 g |

Temperatures & operating conditions

Lifespan

| Number of switching cycles | 100000 |
|--|--------|
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

Additional product data

| Base (standard designation) | E27 |
|-----------------------------|--|
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Frosted |
| Product remark | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

Capabilities

| Dimmable | No |
|----------|----|
|----------|----|

Certificates & Standards

| Energy efficiency class | F ¹⁾ |
|-------------------------|-----------------|

| Energy consumption | 5.00 kWh/1000h |
|--|-----------------|
| Type of protection | IP20 |
| Standards | CE / CB / REACH |
| Photobiological safety group acc. to EN62778 | RG0 |

¹⁾ Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

Country-specific categorizations

| Order reference | VALUE CLA404,9W |
|---|-----------------|
| Energy labelling regulation data acc EU 2019/2015 | |
| Light source can-type (or other electric interface) | F97 |

| Light source cap-type (or other electric interface) | E27 |
|---|---|
| Correlated colour temperature type | SINGLE_VALUE |
| Length | 95.00 mm |
| Height | 55.00 mm |
| Width | 55.00 mm |
| Displacement factor | 0.5 |
| EPREL ID | 1403218,523304,1381362,1857036,1855183 |
| Model number | AC31146,AC24702,AC44911,AC55979,AC56431,AC55979 |

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

| | Documents and certificates | Document name |
|-----|----------------------------|---|
| PDF | Declarations of conformity | EC Declaration of Conformity CLA Non Dim AC31141-56 AC31177-9 AC34531-3 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075476059 | Folding box | 169 mm x 55 mm x 102 mm | 93.00 g | 0.95 dm ³ |
| 4058075476066 | Shipping box 30 | 355 mm x 290 mm x 120 mm | 1291.00 g | 12.35 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.