

# WLD+40012\_SMART

WLD+40012\_SMART

---



---

Power	<b>17 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000/4000/6000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>40 °</b>	UGR	<b>&lt;19</b>
Degree of protection (IP)	<b>IP20</b>		

---

## Technical data

---


Code	WLD+40012_SMART
Power	17 W
Nominal current	375 mA
Voltage	48 V
Energy consumption	17 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1700 lm (360°)
Luminous flux**	850 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	1500 cd
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	40 °
UGR	<19
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	330x23x42 mm
For use	Inside
Assembly method	NA SZYBĘ
Application	Inside
Made in	PRC
Other	CCT/DIM ,




## Related documents

---



 User manual



 Declaration of Conformity



<p>48V </p> <p>45 mm 303 mm 29 mm</p> <p>Die Montage erfolgt über ein einfaches Klick-System zusätzlich lässt sich die Leuchte je nach Bedarf verschieben</p>	<p>48V </p> <p>45 mm 303 mm 29 mm</p> <p>Luminaire assembly within the track on "click" and its free arrangement</p>	
---	--	--

