

Produktdetails

62764-82-WL-500

62764-82-WL-500 WD 180 flex multi sens. WL



Allgemeine Informationen

| | |
|---------------|--|
| Typ | 62764-82-WL-500 |
| Bestellnummer | 2CKA006200A0236 |
| EAN | 4011395292655 |
| Beschreibung | 62764-82-WL-500 WD 180 flex multi sens. WL |

| | |
|------------------|---|
| Langbeschreibung | <p>Movement detector sensor with with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times.</p> <p>For detection down to the floor. For detection in stairwells. With 4 detection levels. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Remote operation via the Bluetooth and smartphone/tablet app.</p> <p>Multi-lens: suitable also for mounting heights of 2.20 m. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 54 sectors with 224 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U.</p> |
|------------------|---|

Installation / Montage

| | |
|--------------------------------|--------------------|
| Betriebs- und Montageanleitung | No document needed |
|--------------------------------|--------------------|

Technische Daten

| | |
|------------------------------------|---|
| Datenblatt, technische Information | No document needed |
| Geeignet für | 2CKA006800A3042 2CKA006800A3048 2CKA006800A3045 2CKA006500A0013 2CKA006800A3051 |
| Unterstützte Bussysteme | free@home |
| Produktreihe | Busch-flexTronics® Busch-free@home® |
| Minimalste Umschaltzeit | einschalten 30 Sekunde(n) |
| Montageart | Flush Mounted |
| Werkstoff | Thermoplastischer Kunststoff |
| Ausführung | Bewegungssensor |
| RAL Nummer | RAL 1013 - perlweiß |
| Farbe | elfenbeinweiß |
| Chemische Batteriezusammensetzung | Lithium, nicht aufladbar |
| Batterieart | Knopfzelle |
| Batteriegewicht | 0.07 g |
| Anwendungsbereich | Elektrische Last- und Lichtsteuerung |

Umwelt

| | |
|---------------------|--|
| Umgebungstemperatur | -5...45 °C |
| Schutzart | IP20 |
| RoHS Status | nach EU-Richtlinie 2015/863 22. Juli 2019 (RoHS 3) |
| RoHS Information | 2CKA200000E7425 |
| REACH Erklärung | 2CKA309999E9999 |

Abmessungen

| | |
|---------------------|-------|
| Breite des Produkts | 63 mm |
| Höhe des Produkts | 63 mm |
| Tiefe des Produkts | 44 mm |
| Nettogewicht | 34 g |

Bestelldaten

| | |
|------------------------------------|----------------|
| Mindestbestellmenge | 1 Stück |
| Menge Verpackungseinheit 1 | Karton 1 Stück |
| Bruttogewicht Verpackungseinheit 1 | 0.105 kg |
| Zolltarifnummer | 85389099 |

Herkunftsland

Deutschland (DE)

Zertifikate und Deklarationen

Konformitätserklärung -
CE

No declaration needed

Klassifizierungen

ETIM 8

EC000138 - Bewegungsmelder-Sensor

ETIM 9

EC000138 - Bewegungsmelder-Sensor

WEEE Kategorie

5. Geräte, bei denen keine der äußeren Abmessungen mehr als 50 cm beträgt
(Kleingeräte)

WEEE B2C / B2B

B2C

CN8

8538 90 99

eClass

V11.0 : 27144008

Kategorien

Niederspannungsprodukte und Systeme → Haus- und Gebäudeautomation → free@home → Bedienen → Solo → Bewegungsmelder

