



Lynx Wallpack



- Robust wall mounted luminaire for general accent illumination and suitable for education, commercial, industrial applications
- Integral emergency option provides downward illumination with a beam angle of 60°
- Die-cast aluminium body with vandal resistant polycarbonate Fresnel lens diffuser
- Tamper-proof allen key screws supplied as standard
- Multiple conduit entry and BESA box fixing points
- Photocell and sensor options
- Powered by Tridonic



Emergency Mode
Beam Angle



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 25°C	L70 56,000	Ra 80	6	25°x75°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	LM/W	TRADE
ALWPLED	Cool White	29W	4000K	2073lm	71lm	£161.00

CODE (OPTIONS)	DESCRIPTION	TRADE	CODE (OPTIONS)	DESCRIPTION	TRADE
/M3	Emergency	+ £90.00	/DD	Digital Dimming (DD1/DD3/DD4)	+ £95.00
/PC	Electronic Photocell	+ £36.00	/MWS	Integral Microwave Sensor	+ £60.00
			/CF	Corridor Function	+ £37.00