





Cabur Solar connector splicing female 10mm2

Code	IS24243N
Type	KX04VF100N
HS code	85366990
TECHNICAL FEATURES	
Application	Cable type
Connector type	Female
Max. applicable voltage	1500 Vdc
Max. applicable current	60 (A)
Cable section	10 (mm ²)
PIN diameter	4 (mm)
Pliers to use	
Fixed matrix	IS3110
PIN material	Tinned Copper
Insulation material	PPE / PA
Contact resistance Rc	< 0.25 (mΩ)
Nut Cap locking force	1.5 – 1.8 (Nm)
Operating temperature range	-40...+85 (°C)
Protection degree	IP68 (1m, 1h)
Flame class	UL94-V0
Packaging	100 (10 bag for every box, every single bag contains 10 plastic shell and 10 metallic PIN.)
ACCESSORIES	
Open-end spanner and unlocking tool	
cod. unlocking tool	IS4SBLOCKN
Quantity / Package	2 pieces
Caps	
Male	IS52400N
Female	IS51400N
Operating temperature range	-40...+85
Protection degree	IP67
Flame class	UL94-V0
Quantity / Package	50 pieces
SPARE COMPONENTS	
Plastic shell	
Metallic PIN wound on reel	
APPROVALS AND MARKINGS 	



1 (1) IS14242N replace the code IS14242.2 (2) IS24243N replace the code IS24243.

DESCRIZIONE DEL PRODOTTO

KX04VF10N Cabur Solar connector splicing female 10mm2