

# WLD+40010\_DALI

WLD+40010\_DALI

---



---

Power	<b>22 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>100 °</b>	Degree of protection (IP)	<b>IP20</b>

---


## Technical data

Code	WLD+40010_DALI
Power	22 W
Nominal current	435 mA
Voltage	48 V
Energy consumption	22 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	tuobo
Power factor	1
Useful luminous flux*	2300 lm (360°)
Luminous flux**	1060 lm (360°)
Lamp efficacy	105 lm/W
Luminous intensity	360 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>90
Light source included	Yes
Producer of LED diodes	osram
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	902x23x42 mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC
Other	DALI ,



## Related documents



 Declaration of Conformity

SYSTEM SHIFT  
CLICK & SHIFT



48V

5 lat gwarancji  
pięć lat warranty

Montaż oprawy w obrobie szyny na „click” oraz  
możliwość swobodnego jej przesuwania

