

PRODUCT-DETAILS

OS630D22N2P

OS630D22N2P SWITCH FUSE



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | OS630D22N2P |
| Code de produit | 1SCA022825R4450 |
| EAN | 6417019283609 |
| Description courte | OS630D22N2P SWITCH FUSE |
| Description longue | Switch Fuses,Front Operated,4-pole,22 (Between the Poles),DIN,3,Handle and shaft included,Switched - With Solid Link |

Circular Value

| | |
|---|-----------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| Informations RoHS | 1SCC011020D0201 |

Commande

| | |
|------------------|--------------|
| Quantité minimum | 1 pièce |
| Code douanier | 85365080 |
| Pays d'origine | Finland (FI) |

Popular Downloads

| | |
|--|-----------------|
| Fiche produit, informations techniques | 1SCC311013C0201 |
| Instructions et manuels | 1SCC311016M0210 |

Dimensions

| | |
|----------------------|----------------------|
| Produit Largeur Net | 429 mm |
| Produit Hauteur Net | 306 mm |
| Produit Longueur Net | 233 mm |
| Poids net | 19.04 kg 41.98 lb |

Technique

| | |
|--|--|
| Rated Operational Current AC-21A (I_e) | (500 V) 630 A (690 V) 630 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A |
| Rated Operational Current AC-23B (I_e) | (380 ... 415 V) 630 A (500 V) 630 A (690 V) 630 A |
| Rated Operational Power AC-23A (P_e) | (220 ... 240 V) 200 kW (400 V) 355 kW (415 V) 355 kW (500 V) 450 kW (690 V) 630 kW |
| Courant thermique conventionnel à l'air libre (I_{th}) | $\Theta = 40\text{ °C}$ 630 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 570 A |
| Tension assignée de tenue aux chocs (U_{imp}) | 12 kV |
| Tension assignée d'isolement (U_i) | 1000 V |
| Tension | Circuit principal 690 V AC |
| Courant assigné de courte durée admissible (I_{cw}) | for 1 s 18 kiloampere rms |
| Rated Conditional Short-Circuit Current (I_{nc}) | (690 V) 80 kA |
| Power Loss | at Rated Operating Conditions per Pole 60 W |
| Degré de pollution | 3 |
| Handle Type | Pistol handle and shaft included |
| Fourth Pole Position | Right Side |

| | |
|------------------------------|--|
| Fourth Pole Type | Switched - With Solid Link |
| Switches Operating Mechanism | 22 (Between the Poles) |
| Position of Line Terminals | Top In - Bottom Out, Bottom In - Top Out |
| Taille de fusible | NH3 |
| Fuse System | DIN |
| Mode de fonctionnement | Front Operated |
| Normes et standards | IEC 60947-3 |
| Type de montage | Base mounting |
| Nombre de pôles | 4 |
| Type de borne | Lug terminals |
| Terminal Width | 39 mm |
| Couple de serrage | 50 ... 75 N·m |
| Courant nominal (I_n) | Main Circuit 630 A |

Technique UL/CSA

| | |
|-------------------|---------------|
| Couple de serrage | 50 ... 75 N·m |
|-------------------|---------------|

Environnement

| | |
|-------------|--|
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Certificats et Déclarations (Numéro de document)

| | |
|-----------------------------------|---|
| CCC Certificate | CCC OS630-800 2016 |
| Déclaration de Conformité - CE | 1SCC311112D2704 |
| DNV GL Certificate | 1SCC311131D0202 |
| EAC Certificate | EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_ .pdf |
| REACH Declaration | 1SCC011021D0201 |

Emballage

| | |
|--------------------------------|---------------------|
| Emballage Niveau 1 Unités | box 1 pièce |
| Emballage Niveau 1 Largeur | 328 mm 12.91 in |
| Emballage Niveau 1 Longueur | 453 mm 17.83 in |
| Emballage Niveau 1 Hauteur | 260 mm 10.24 in |
| Emballage Niveau 1 Poids | 19.9 kg 43.87 lb |
| Emballage Niveau 1 EAN | 6417019283609 |

Classifications

| | |
|--------------------------------|--|
| Code de classification d'objet | Q |
| ETIM 7 | EC001040 - Fuse switch disconnecter |
| ETIM 8 | EC001040 - Fuse switch disconnecter |
| ETIM 9 | EC001040 - Fuse switch disconnecter |
| eClass | V11.1 : 27371401 |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Finland) | 3661532 |

Catégories

Produits basse tension → Interrupteurs → Interrupteurs à fusibles

