

# SLI035070WW\_35W\_DALI

SLI035070WW\_35W\_DALI



Power	<b>35 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3850 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

---

Code	SLI035070WW_35W_DALI
Power	35 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3850 lm (360°)
Luminous flux**	3850 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	25000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x10 mm
Mounting hole	600x600 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC