

# PRODUCT DATASHEET HE SL 28 W/865

SMARTLUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency






# TECHNICAL DATA

# Electrical data

Nominal wattage	28 W
Construction wattage	27.90 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	86

# Photometrical data

Luminous flux	2400 lm
Luminous efficacy	85 lm/W
Luminous flux at 25 °C	2400 lm
Luminous flux at 35 °C	2750 lm
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.92
Rated LLMF at 6,000 h	0.91
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	86



349641\_FL\_865

# Dimensions & Weight

Overall length	1149.00 mm
Length with base excl. base pins/connection	1149 mm

Discovering.	10.0
Diameter	16,0 mm
Tube diameter	16 mm
Maximum diameter	16 mm
Product weight	90.00 g
Temperatures & operating conditions	
Rated ambient temp.w.max.luminous	35.0 °C
Lifespan	
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	HF
Additional product data	
Base (standard designation)	G5
Mercury content	1.2 mg
Capabilities	
Suitable for indoor	Yes
Certificates & Standards	
Energy efficiency class	A+
Energy efficiency class  Energy consumption	A+ 30.69 kWh/1000h
Energy consumption	
Energy consumption  Country-specific categorizations	30.69 kWh/1000h
Energy consumption  Country-specific categorizations  Order reference	30.69 kWh/1000h
Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015	30.69 kWh/1000h  HE 28W/865 SL
Energy consumption  Country-specific categorizations  Order reference  Energy labelling regulation data acc EU 2019/2015  Light source cap-type (or other electric interface)	30.69 kWh/1000h  HE 28W/865 SL  G5

## DOWNLOAD DATA

Photometric and lighting design files	Document name
Spectral power distribution	349641_FL_865

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321335623	Sleeve 1	1,164 mm x 18 mm x 18 mm	109.00 g	0.38 dm <sup>3</sup>
4052899046856	Shipping box 20	1,191 mm x 104 mm x 88 mm	3018.00 g	10.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.