

ARTEMIDA MINI

SLI033023WW_PW

See
more

LED luminaire ARTEMIDA MINI, with power regulation on the power supply (6,5-20 W), high light efficacy 115 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.




| | | | |
|--------------------|-----------------|---------------------------|--------------|
| Power | 6,5-20 W | Voltage | 230 V |
| Colour temperature | 3000 K | Colour of light | WW |
| Beam angle | 36, 60 ° | Degree of protection (IP) | IP20 |

Technical data


| | |
|------------------------------|--|
| Code | SLI033023WW_PW |
| Power | 6,5-20 W |
| Nominal current | 90 mA |
| Voltage | 230 V |
| Energy consumption | 20 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | Yes |
| Power factor | 0.9 |
| Useful luminous flux* | 2300 lm (360°) |
| Luminous flux** | 600-1700 lm (360°) |
| Lamp efficacy | 115 lm/W |
| Luminous intensity | 3800 cd |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 36, 60 ° |
| RA | >90 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum, PLASTIC |
| Degree of protection (IP) | IP20 |
| Colour | Black |
| Dimension (AxBxC) | 75x78x110 mm |
| For use | Inside |
| Assembly method | on track |
| Application | Inside |
| Made in | PRC |
| Other | DIP SWITCH - adjustable power of luminaire , |

Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model

