

NOCTIS LUX 2

SLI029037CW_CZUJNIK



See
more

Floodlight NOCTIS LUX 2, with a power of 10 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. It shines with a cold light (6000K). Designed for surface mounting.

IP44



Power	10 W	Voltage	230 V
Luminous flux*	850 lm (120°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	100 °
Degree of protection (IP)	IP44		


Technical data

Code	SLI029037CW_CZUJNIK
Power	10 W
Nominal current	70 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	850 lm (120°)
Luminous flux**	830/850 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	160x104x25 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



Related documents



 Declaration of Conformity



 Photometric file

	<p>Radiator skutecznie odprowadzający ciepło</p> <p>Trwałe diody LED</p> <p>Hartowane szkło</p> <p>Klasa szczelności IP65</p> <p>Uchwyt regulowany</p> <p>Gumowany kabel 30cm</p> <p>Uchylny czujnik ruchu PIR</p> <p>Długi uchwyt</p>	
<p>Regulacja czasu świecenia min: 10 sec ± 3 sec max: 7 min ± 12min</p> <p>Regulacja czułości/zasięgu detekcji 2-10m (< 24°C)</p> <p>Regulacja czujnika zmierzchowego 3-2000 LUX</p>	<p>104 mm</p> <p>83 mm</p> <p>160 mm</p> <p>25 mm</p>	<p>104 mm</p> <p>83 mm</p> <p>160 mm</p> <p>25 mm</p>