

PRODUCT-DETAILS

MC2C400ATWID-RAIL

MC2C400ATWID-RAIL Mini Contactor 51 ... 90 V DC - 4 NO - 0 NC - Schroef



Algemene informatie

Type	MC2C400ATWID-RAIL
Artikelnummer	1SAL247476R9912
EAN	4013614548260
Omschrijving	MC2C400ATWID-RAIL Mini Contactor 51 ... 90 V DC - 4 NO - 0 NC - Schroef
Omschrijving	The MC2C400ATWID-RAIL mini contactor is a dimension optimized 4 pole contactor with screw terminals. This device is a great solution when high performances are needed but the space is limited. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 5.5 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. The product is suitable for wall or rail mounting.

Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85365080

Popular Downloads

Instructies en handleidingen	2CDC103061M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product netto breedte	45 mm
Product netto hoogte	48 mm
Product netto diepte	68 mm
Product netto gewicht	0.25 kg

Technical

Aantal polen	4
Type minicontactor	Mini Contactor
Nominaal bedrijfsvoltage	Main Circuit 690 V AC Main Circuit 440 V DC
Toegekende frequentie (f)	Control Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz Main Circuit DC
Nominale impuls grensvoltage (U_{imp})	Main Circuit 6 kV
Nominaal isolatievoltage (U_i)	750 V
Aantal hoofdcontacten NC	0
Aantal hoofdcontacten NO	4
Nominale bedrijfsstroom AC-1 (I_e)	(690 V) 55 °C 20 A (690 V) 70 °C 16 A (230 V) 55 °C 20 A (230 V) 70 °C 16 A (400 V) 55 °C 20 A (400 V) 70 °C 16 A (500 V) 55 °C 20 A (500 V) 70 °C 16 A
Nominale bedrijfsvermogen AC-3 (P_e)	(230 V) Three Phase 3 kW (400 V) Three Phase 5.5 kW (500 V) Three Phase 5.5 kW (690 V) Three Phase, NO 4 kW
Nominale kortstondige grensstroom (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A
Aantal hulpcontacten NC	0
Aantal hulpcontacten NO	0
Conventionele vrije-lucht thermische stroom (I_{th})	Main Circuit 20 A
Nominale stuurstroomkringspanning (U_c)	51 ... 90 V DC
Spoel operationele limieten	(acc. to IEC 60947-4-1) for DC supply U_c Min. ... U_c Max. (at $\theta \leq 55$ °C)
Beschermingsgraad	Control Circuit Terminals IP20 Main Circuit Terminals IP20
Mechanische duurzaamheid	10000000 cycle
Maximale elektrische schakelfrequentie	(AC-1) 300 omwentelingen per uur (AC-15) 360 omwentelingen per uur (AC-3) 1200 omwentelingen per uur (DC-1) 600 omwentelingen per uur (DC-13) 360 omwentelingen per uur (DC-3) 600 omwentelingen per uur
Verbindingscapaciteit hoofdcircuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1x 0.75 ... 4 mm ² Rigid 2x 0.75 ... 2.5 mm ²

Verbindingscapaciteit controlecircuit	Flexible with Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Kabelstriplengte	Control Circuit 9 mm Main Circuit 9 mm
Aanhaalmoment	Control Circuit 0.8 N·m Main Circuit 0.8 ... 1.0 N·m
Aanbevolen schroevendraaier	Pozidriv 2
Montage op DIN-rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Vermogensverlies	at Rated Operating Conditions AC-1 per Pole 0.7 W
Normen	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximale bedrijfsspanning UL/CSA	Main Circuit 600 V AC
Vollast amps motorgebruik	(115 V AC) Single Phase 9.8 A (200 V AC) Three Phase 11 A (220 ... 240 V AC) Three Phase 9.6 A (230 V AC) Single Phase 12 A (440 ... 480 V AC) Three Phase 11 A (550 ... 600 V AC) Three Phase 11 A
Paardenkrachtklasse UL/CSA	(115 V AC) Single Phase 0.5 Hp (200 V AC) Three Phase 3 Hp (220 ... 240 V AC) Three Phase 3 Hp (230 V AC) Single Phase 2 Hp (440 ... 480 V AC) Three Phase 7.5 Hp (550 ... 600 V AC) Three Phase 10 Hp
Algemeen gebruik klasse UL/CSA	(600 V AC) 20 A
Verbindingscapaciteit hoofdcircuit UL/CSA	Stranded 1/2x 18-12 AWG
Aanhaalmoment UL/CSA	Control Circuit 7 in-lb Main Circuit 7 in-lb

Environmental

Omgevingsluchttemperatu ur	Werking -40 ... +70 °C Opslag -55 ... +80 °C
Maximale werkhoo gte toegestaan	3000 m
Schokweerstand vol gens IEC 60068-2-27	11 ms Pulse 25g
Weerstand tegen trill ingen volgens IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations

BV-certificaat	1SAA971000-0201
CB-certificaat	1SAA971000-2001
CQC-certificaat	CQC2019010304197131
Declaration of Conformity - CCC	2020980304001602

Conformiteitsverklaring - CE	1SAD101100-3201
Declaration of Conformity - UKCA	1SAD201100-3201
RINA-certificaat	1SAA971001-0801
UL-certificaat	E191658-19880826

Container Information

Pakketniveau 1 Units	doos 1 stuk
Pakketniveau 1 Breedte	46 mm
Pakketniveau 1 Hoogte	70 mm
Pakketniveau 1 Lengte	49 mm
Pakketniveau 1 Bruto gewicht	0.255 kg
Pakketniveau 1 EAN	4013614548260
Pakketniveau 2 Units	doos 10 stuk
Pakketniveau 2 Breedte	243 mm
Pakketniveau 2 Hoogte	80 mm
Pakketniveau 2 Lengte	106 mm
Pakketniveau 2 Bruto gewicht	2.61 kg
Pakketniveau 2 EAN	4013614548420

Classifications

Object classificatiecode	Q
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Magneetschakelaar
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Magneetschakelaar
eClass	V11.0 : 27371003
UNSPSC	39121529
E-Number (Finland)	3709725

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Magneetschakelaars → Minischakelaars

