

PRODUCT-DETAILS

XRG1-50/5-3P-EFM

XRG1-50/5-3P-EFM Switch disconnector fuse



| General Information | |
|---|---|
| Extended Product Type | XRG1-50/5-3P-EFM |
| Product ID | 1SEP204481R1501 |
| EAN | 3800161650789 |
| Catalog Description | XRG1-50/5-3P-EFM Switch disconnector fuse |
| Long Description | Three pole Switch Disconnector Fuse for 50mm busbar distance and 5mm busbar thickness, including Electronic Fuse Monitoring |
| Circular Value | |
| | 0.1///00.1671.5650 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 1SCC011021D0201 |
| RoHS Information | 1SCC011020D0201 |
| Ordering | |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363000 |
| Country of Origin | Bulgaria (BG) |

XRG1-50/5-3P-EFM 2

| Popular Downloads | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 1SEC313002D0201 |
| Instructions and Manuals | 9AKK107492A8856 |
| Mechanical Drawings | 9AKK107680A0378 |

| Dimensions | |
|----------------------------|---------|
| Product Net Width | 590 mm |
| Product Net Height | 100 mm |
| Product Net Depth / Length | 335 mm |
| Product Net Weight | 7.01 kg |

| Technical | |
|---|---|
| Rated Operational Current AC-22B (I _e) | (500 V) 250 A (690 V) 250 A |
| Rated Operational Current AC-23A (I _e) | (500 V) 250 A (690 V) 250 A |
| Rated Impulse Withstand Voltage (U _{imp}) | 8 kV |
| Rated Insulation Voltage (U _i) | 1 kV |
| Rated Operational Voltage | 690 V AC |
| Power Loss | at Rated Load 70 W |
| Distance Between Phases | 50 mm |
| Busbar Dimensions | Thickness 5 mm |
| Fuse Size | NH1 |
| Fuse System | DIN |
| Operating Mode | Manual |
| Standards | IEC60947-3 |
| Number of Poles | 3 |
| Degree of Protection | acc. to IEC 60529 Front IP41 |
| Terminal Type | Bolt |
| Rated Current (In) | 250 A |
| Rated Voltage (U _r) | 690 V AC |
| Electronic Fuse Monitoring | Yes |
| Utilization Category | Switching of motor loads or other highly inductive loads - frequent actuation (AC-23A) |
| | Switching of mixed resistive and inductive loads, including moderate overloads - occasional actuation (AC-22B) |

| Environmental | |
|---------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20190927 |

| Certificates and Declarations | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC311166D2701 |

XRG1-50/5-3P-EFM 3

REACH Declaration 1SCC011021D0201

| Container Information | |
|-----------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 600 mm |
| Package Level 1 Depth / Length | 340 mm |
| Package Level 1 Height | 107 mm |
| Package Level 1 Gross Weight | 7.47 kg |

| Classifications | |
|-----------------|---|
| ETIM 7 | EC001040 - Fuse switch disconnector |
| ETIM 8 | EC001040 - Fuse switch disconnector |
| ETIM 9 | EC001040 - Fuse switch disconnector |
| eClass | V11.1: 27371401 |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems \rightarrow Fusegear \rightarrow Switch Disconnector Fuse

