

# SLI047100NW\_PW

SLI047100NW\_PW



See  
more



Power **75 W**

Colour temperature **4000 K**

Beam angle **90 °**

Voltage **230 V**

Colour of light **Neutral white**

Degree of protection (IP) **IP40**

## Technical data


---

Code	SLI047100NW_PW
Power	75 W
Nominal current	335 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.98
Useful luminous flux*	13500 lm (360°)
Luminous flux**	12750 lm (360°)
Lamp efficacy	180 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/PC
Degree of protection (IP)	IP40
Colour	White
Dimension (AxBxC)	1438x65x40 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INTERNAL
Made in	PRC
Other	Max ilość opraw na zabezpieczenie nadprądowe: ,


## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

