

Produktdetails

62762-81-WL-500

62762-81-WL-500 WD 180 flex conf. sens. WL



Allgemeine Informationen

Typ	62762-81-WL-500
Bestellnummer	2CKA006200A0166
EAN	4011395292211
Beschreibung	62762-81-WL-500 WD 180 flex conf. sens. WL

Langbeschreibung	<p>Movement detector sensor with with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times.</p> <p>./. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Works with free@home. Remote operation via the Bluetooth and smartphone/tablet app. Programming via Bluetooth with the ABB-free@home® app or via the web interface of the System Access Point. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 14 sectors with 56 switching segments.</p> <p>Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U. For LED touch dimmer insert flex, 1gang, 64851 U.</p>
------------------	--

Installation / Montage

Betriebs- und Montageanleitung	No document needed
--------------------------------	--------------------

## Technische Daten

Datenblatt, technische Information	No document needed
Geeignet für	2CKA006800A3042 2CKA006800A3048 2CKA006800A3045 2CKA006500A0013 2CKA006800A3051
Unterstützte Bussysteme	free@home
Produktreihe	Busch-flexTronics® Busch-free@home®
Schalterdesign	63x63 future® linear Busch-axcent® Busch-axcent pur Busch-dynasty® carat®
Minimalste Umschaltzeit	einschalten 30 Sekunde(n)
Montageart	Flush Mounted
Werkstoff	Thermoplastischer Kunststoff
Ausführung	Bewegungssensor
RAL Nummer	RAL 7021 - schwarzgrau
Farbe	anthrazit
Chemische Batteriezusammensetzung	Lithium, nicht aufladbar
Batterieart	Knopfzelle
Batteriegewicht	0.07 g
Anwendungsbereich	Elektrische Last- und Lichtsteuerung

## Umwelt

Umgebungstemperatur	-5...45 °C
Schutzart	IP20
RoHS Status	nach EU-Richtlinie 2015/863 22. Juli 2019 (RoHS 3)
RoHS Information	2CKA200000E7367
REACH Erklärung	2CKA309999E9999

## Abmessungen

Breite des Produkts	63 mm
Höhe des Produkts	63 mm
Tiefe des Produkts	35 mm
Nettogewicht	34 g

## Bestelldaten

Mindestbestellmenge	1 Stück
Menge Verpackungseinheit 1	Karton 1 Stück
Bruttogewicht Verpackungseinheit 1	0.105 kg
Zolltarifnummer	85389099
E-Nummer (Finnland)	2815701
Herkunftsland	Deutschland (DE)

---

## Zertifikate und Deklarationen

---

Konformitätserklärung - CE	No declaration needed
----------------------------	-----------------------

---



---

## Klassifizierungen

---

ETIM 8	EC000138 - Bewegungsmelder-Sensor
ETIM 9	EC000138 - Bewegungsmelder-Sensor
WEEE Kategorie	5. Geräte, bei denen keine der äußeren Abmessungen mehr als 50 cm beträgt (Kleingeräte)
WEEE B2C / B2B	B2C
CN8	8538 90 99
eClass	V11.0 : 27144008

---



---

## Kategorien

---

Niederspannungsprodukte und Systeme → Haus- und Gebäudeautomation → free@home → Bedienen → Solo → Bewegungsmelder

