


NH fuse enclosure

GST 4115-400



GST 4115-400

NH fuse enclosure

CUSTOMIZABLE

Productnumber: 04611501

Dimensions: 320 x 640 x 254 mm

NH bus-mounting fuse empty enclosure for switchgear - Industrial Quality -, 1 x NH 1 fuse switch disconnecter enclosure, Screw connection M10, Output on bottom, on 5-pole busbar, N terminal 16 - 120 mm², PE terminal 16 - 120 mm², 4 x housing connectors (GGV)

on busbar system 400 A, with transparent cover



Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Protection class:	II
Type of protection:	IP65
Rated current:	400 Ampere
UL Type Rating:	3R

Dimensions

Width:	320 mm
Length:	640 mm
Height:	254 mm

Material characteristics

suitable for exterior use:	yes
Industry quality:	yes
Halogen free:	yes
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Impact strength:	IK08
Cover screw torque:	2.5 Nm
Stackable:	yes

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-25 °C
Max. ambient temperature:	40 °C
24h ambient temperature:	35 °C

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate, glass-fibre reinforced
Sealing material:	Polyurethane
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

[07251401 - GFS 14-m - Flange set](#)

[07505601 - GSV 56 - Busbar connector](#)

[07673101 - KPK NH 1 - Prism terminal](#)

[07674101 - KRK NH 1 - Frame clamp for NH1 isolator](#)

[07672101 - KSK NH 1 - Lug terminal](#)