

PRODUCT-DETAILS

# P9PLFVJR

## P9PLFVJR LED block



### Informations générales

Extension du type de produit	P9PLFVJR
Code de produit	1SFA197028R1041
EAN	7320500523957
Description courte	P9PLFVJR LED block
Description longue	The P9PLFVJR LED block is: Modular metal - LED block - Flashing - Red - Illuminated - Front mounting - 120 V This LED block is part of ABB's modular metal range designed for mining, construction and heavy industry applications, combining the highest reliability with the full flexibility of a modular range.

### Commande

Quantité minimum	10 pièce
Code douanier	8539500000

### Popular Downloads

Fiche produit, informations techniques	1SFC151007C02_
Instructions et manuels	1SFC151011M0201

---

## Dimensions

---

Produit Largeur Net	9.8 mm
Produit Hauteur Net	39.5 mm
Produit Longueur Net	56 mm
Poids net	0.019 kg

---



---

## Technique

---

Température de l'air ambiant	Operation -30 ... 70 °C Storage -40 ... +70 °C
Couleur	Red
Voyant	Illuminated
Type de lampe	120 VAC, Integrated LED
Fonction	Flashing
Type de montage	Front mounting
Indice de protection	Terminals IP20
Degré de pollution	3
Fréquence assignée (f)	50 / 60 Hz
Tension	120 V AC
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.75...2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.75...2.5 mm <sup>2</sup> Flexible 1 x 0.75 ... 2.5 mm <sup>2</sup> Flexible 2 x 0.75 ... 2.5 mm <sup>2</sup> Solid 1 x 0.75...2.5 mm <sup>2</sup> Solid 2 x 0.75...2.5 mm <sup>2</sup>
Type de raccordement	Screw Clamp
Type de borne	Screw Terminals
Couple de serrage	0.9 N·m
Wire Stripping Length	8 mm

---



---

## Technique UL/CSA

---

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

---



---

## Environnement

---

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CMT2019-005862
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Business

---



---

## Certificats et Déclarations (Numéro de document)

---

Certificat BV	2CMT2019-005867
---------------	-----------------

---

CB Certificate	2CMT2019-005874
CQC Certificate	CQC2019010304237361
Certificat CSA	2CMT2019-005868
Certificat ecULus	2CMT2019-005868
Declaration of Conformity - CCC	2020980304001528
Déclaration de Conformité - CE	2CMT2019-005862
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	2CMT2019-005876
Certificat RINA	2CMT2019-005866
Certificat UL	2CMT2019-005868

## Emballage

Emballage Niveau 1 Unités	bag 1 pièce
Emballage Niveau 1 Largeur	120 mm
Emballage Niveau 1 Longueur	50 mm
Emballage Niveau 1 Hauteur	180 mm
Emballage Niveau 1 Poids	0.019 kg
Emballage Niveau 1 EAN	7320500523957

## Classifications

ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39122221
Code de catégorie granulaire IDEA (IGCC)	5219 >> Switch part or accessory
E-Number (Finland)	2314875

## Catégories

Produits basse tension → Produits de Contrôle, Protection et sécurité machines → Unités de commande et de signalisation → Modular Metal Range P9M

