


BCO MOD ML2 BE HF 5 (927 070)


- LifeCheck arrester monitoring and integrated status indication
- Two-pole protection module for optimal protection of two single lines of high-frequency signal circuits
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_A -2$ and higher



Figure without obligation



Basic circuit diagram BCO MOD ML2 BE HF 5



Dimension drawing BCO MOD ML2 BE HF 5

Protection module with a width of 6 mm for BLITZDUCTORconnect combined arrester with status indication for protecting two single lines of high-frequency transmissions sharing a common reference potential as well as unbalanced interfaces.

Type	BCO MOD ML2 BE HF 5
Part No.	927 070
SPD class	TYPE 4 PI
Impulse category	D1, C1, C2, C3, B2
Nominal voltage (U_N)	5 V
Max. continuous operating voltage (d.c.) (U_C)	8.5 V
Max. continuous operating voltage (a.c.) (U_C)	6.0 V
Nominal current at 70 °C (I_N)	0.75 A
D1 Total lightning impulse current (10/350 μ s) (I_{imp})	3 kA
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	1.5 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	10 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	5 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 50 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 70 V
Voltage protection level line-line for I_n C1 (U_p)	≤ 50 V
Voltage protection level line-PG for I_n C1 (U_p)	≤ 70 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 15 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 15 V
Series resistance per line	1 ohm(s)
Cut-off frequency line-PG (f_c)	100 MHz
Capacitance line-line (C)	≤ 20 pF pF
Capacitance line-PG (C)	≤ 23 pF pF
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Degree of protection (with plugged-in protection module)	IP 20
Plugs into	BCO base part
Earthing via	BCO base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL, CSA, EAC, ATEX, IECEx, CCC, SIL
ATEX approvals	TÜV 20 ATEX 8527 X: II 3G Ex ec IIC T4 Gc
IECEx approvals	IECEx TUR 20.0063X: Ex ec IIC T4 Gc
China Compulsory Certification	CCC no. 2021312304001192
Extended technical data:	-----
- Max. discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG] (I_{max})	20 kA
- Discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG]	10 kA (10x)
- Voltage protection level line-PG at 1 kV/ μ s C3 after being subjected to I_{max} (U_p)	≤ 15 V
Weight	14 g
Customs tariff number	85363010
GTIN	4013364410183
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.