

PRODUCT DATASHEET

L 58 W/965

LUMILUX® DE LUXE T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Ideal where color rendering is an important factor
- Public buildings
- Shops
- Supermarkets and department stores
- Industry

Product benefits

- Natural colors

Product features

- Very good color rendering index
- Dimmable




TECHNICAL DATA

Electrical data

Nominal wattage	58 W
Construction wattage	60.90 W
Nominal voltage	110 V
Nominal current	0.67 A

Photometrical data

Luminous flux	4550 lm
Luminous efficacy	75 lm/W
Light color (designation)	LUMILUX DE LUXE Cool Daylight
Color temperature	6500 K
Color rendering index Ra	≥ 90
Light color	965
Rated LLMF at 2,000 h	0.93
Rated LLMF at 4,000 h	0.90
Rated LLMF at 6,000 h	0.88
Rated LLMF at 8,000 h	0.87
Rated LLMF at 12,000 h	0.85
Rated LLMF at 16,000 h	0.83
Rated LLMF at 20,000 h	0.82



Dimensions & Weight

Overall length	1514.20 mm
Length with base excl. base pins/connection	1500 mm
Diameter	26.00 mm
Tube diameter	26 mm

Product weight	207.00 g
----------------	----------

Lifespan

Lifespan	20000 h
Service life	16000 h ¹⁾
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.99
Rated lamp survival factor at 6,000	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.90
Rated lamp survival factor at 20,000 h	0.50
Lifespan B50	20000 h

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg

Capabilities

Dimmable	Yes
----------	-----

Certificates & Standards

Energy efficiency class	G
Energy consumption	61.00 kWh/1000h

Country-specific categorizations

ILCOS	FD-58/965-E-G13-26/1500
Order reference	L 58W/965

Energy labelling regulation data acc EU 2019/2015




Lighting technology used	OTHER_FL
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G13
Connected light source (CLS)	No
Color-tuneable light source	No

Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	1514.20 mm
Height	26.00 mm
Width	26.00 mm
Chromaticity coordinate x	0,313
Chromaticity coordinate y	0,327
Beam angle correspondence	SPHERE_360
EPREL ID	546397
Model number	AC34172

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

Documents and certificates	
	Declarations Of Conformity CE
	Certificates
Photometric and lighting design files	
	Spectral power distribution

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321090034	Sleeve 1	1,515 mm x 27 mm x 27 mm	232.00 g	1.10 dm ³
4008321090041	Shipping box 25	1,553 mm x 151 mm x 153 mm	6679.00 g	35.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.