

## EKV1+0 50 VKVBG8W (VKVBG8W)



Figure without obligation

Type	EKV1+0 50 VKVBG8W
Part No.	VKVBG8W
Version	Single-pole
Cable cross-section (phase side)	50 mm <sup>2</sup>
Cable cross-section (earth side)	50 mm <sup>2</sup>
Length of single-pole cable	5000 mm
Cable cross-section	50 mm <sup>2</sup>
Fully insulated	No
Max. short-circuit current I <sub>k</sub> 0.5 s	9.3 kA
Max. short-circuit current I <sub>k</sub> 1 s	6.6 kA
Crimped cable lug	PK1
Standard	EN/IEC 61138 (DIN VDE 0283-3) and EN/IEC 61230 (DIN VDE 0683-100)
Temperature range	-25 °C ... +55 °C
Material (cable)	Al
Material (sheath)	Thermoplastic polymer (flexible PVC compound YM2)
Hole (cable lug)	Ø12.5 mm
Weight	1,51 kg
Customs tariff number	85359000
GTIN	4013364360136
PU	1 Stk

**Attention: Please state the relevant Variant No. when ordering.**

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.