

# WLD+70029WW

WLD+70029WW

---



---

Power	<b>12 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>2700 K</b>	Colour of light	<b>WW</b>
Beam angle	<b>24 °</b>	UGR	<b>&lt;19</b>
Degree of protection (IP)	<b>IP20</b>		

---

## Technical data

---

Code	WLD+70029WW
Power	12 W
Nominal current	240 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	1260 lm (360°)
Luminous flux**	970 lm (360°)
Lamp efficacy	105 lm/W
Luminous intensity	4500 cd
Colour temperature	2700 K
Colour of light	WW
Beam angle	24 °
UGR	<19
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	220x23x42 mm
For use	Inside
Assembly method	NA SZYŃE
Application	Inside
Made in	PRC


## Related documents

---



 User manual



 Declaration of Conformity