


## BXT ML4 BE C 12 (920 362)


- LifeCheck SPD monitoring function
- Additional decoupling with regard to terminal equipment
- For installation in conformity with the lightning protection zone concept at the boundaries from  $0_A - 2$  and higher



Figure without obligation



Basic circuit diagram BXT ML4 BE C 12



Dimension drawing BXT ML4 BE C 12

Space-saving combined lightning current and surge arrester module with LifeCheck feature for protecting two pairs of balanced interfaces with diode protective circuit at the input, current loops (TTY) and optocoupler inputs. If LifeCheck detects thermal or electrical overload, the arrester has to be replaced. This status is indicated contactlessly by the DEHNrecord LC / SCM / MCM reader.

Type	BXT ML4 BE C 12
Part No.	920 362
SPD monitoring system	LifeCheck
SPD class	TYPE 1P1
Nominal voltage ( $U_n$ )	12 V
Max. continuous operating voltage (d.c.) ( $U_c$ )	15 V
Max. continuous operating voltage (a.c.) ( $U_c$ )	10.6 V
Nominal current at 80 °C ( $I_L$ )	0.1 A
D1 Total lightning impulse current (10/350 µs) ( $I_{imp}$ )	10 kA
D1 Lightning impulse current (10/350 µs) per line ( $I_{imp}$ )	2.5 kA
C2 Total nominal discharge current (8/20 µs) ( $I_n$ )	20 kA
C2 Nominal discharge current (8/20 µs) per line ( $I_n$ )	10 kA
Voltage protection level line-line for $I_{imp}$ D1 ( $U_p$ )	≤ 30 V
Voltage protection level line-PG for $I_{imp}$ D1 ( $U_p$ )	≤ 35 V
Voltage protection level line-line at 1 kV/µs C3 ( $U_p$ )	≤ 19 V
Voltage protection level line-PG at 1 kV/µs C3 ( $U_p$ )	≤ 19 V
Series resistance per line	13.8 ohm(s)
Cut-off frequency line-PG ( $f_G$ )	0.85 MHz
Capacitance line-line (C)	≤ 3.2 nF
Capacitance line-PG (C)	≤ 3.2 nF
Operating temperature range ( $T_u$ )	-40 °C ... +80 °C
Degree of protection (with plugged-in protection module)	IP 20
Pluggable into	BXT BAS / BSP BAS 4 base part
Earthing via	BXT BAS / BSP BAS 4 base part
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
SIL classification	up to SIL3 *)
ATEX approvals	DEKRA 11ATEX0089 X: II 3 G Ex nA IIC T4 Gc
IECEx approvals	DEK 11.0032X: Ex nA IIC T4 Gc
CSA & USA Hazloc approvals (1)	2516389: Class I Div. 2 GP A, B, C, D T4
CSA & USA Hazloc approvals (2)	2516389: Class I Zone 2, AEx nA IIC T4
Weight	24 g
Customs tariff number	85363010
GTIN	4013364120587
PU	1 Stk

\*)For more detailed information, please visit [www.dehn-international.com](http://www.dehn-international.com).

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.