

PRODUCT DATASHEET

SUN@Home Planon Plus 600x600mm

SUN@HOME PANELS | Panel luminaires with Human Centric Lighting Technology



Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature

TECHNICAL DATA

Electrical data

| | |
|------------------------|---------------|
| Nominal wattage | 35.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Inrush current | 3 A |
| Power factor λ | ≥ 0.5 |
| Protection class | II |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|----------------------|
| Luminous flux | 2300 lm |
| Total luminous flux of contained light sources | 3250 lm |
| Luminous efficacy | 95 lm/W |
| Color temperature | 2200...5000 K |
| Light color (designation) | Tunable White |
| Color rendering index Ra | > 95 |
| Standard deviation of color matching | < 6 sdc _m |
| Photobiological safety group acc. to EN62778 | RG0 |
| Photobiological safety group acc. to EN62471 | RG0 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 600.00 mm |
| Width | 600.00 mm |
| Height | 56.00 mm |
| Product weight | 3460.00 g |

Materials & Colors

| | |
|---------------|-------|
| Product color | White |
| Housing color | White |

| | |
|-----------------|--------------------|
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|-----------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Mounting location | Ceiling |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 30000 h |
| Number of switching cycles | 15000 |

Emergency lighting

| | |
|--|----------------|
| Type of emergency light operation | Non-maintained |
| Type of emergency operation test | None |
| Luminous flux in maintained operation mode | - |
| Luminous flux in emergency operation mode | - |





Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / ERP / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

DOWNLOAD DATA

| Documents and certificates | |
|--|-------------------------------|
|  | User instruction |
|  | Packaging insert |
|  | Declarations Of Conformity CE |
| CAD/BIM files | |
|  | BIM_Step_3D |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075576056 | Folding box 1 | 76 mm x 622 mm x 623 mm | 4061.00 g | 29.45 dm ³ |
| 4058075576063 | Shipping box 3 | 672 mm x 281 mm x 680 mm | 13494.00 g | 128.41 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.