

# Product Data Sheet

## GW11241


CHORUSMART - Domestic range



Wide range of control devices, sockets for power supply (conforming to national and international standards) signal pick-up, climate control, comfort management, technical alarm signalling and emergency lighting management. The ChoruSmart modular devices are available in five colours, glossy white, satin white, natural beige, satin black and lacquered titanium and in various sizes from 1/2, 1, 2 and 3 modules. Thanks to the mounting supports for rectangular, square and round boxes, endless combinations can be created with the ChoruSmart range of plates.

|  |  |   |                                |
|--|--|---|--------------------------------|
| Category   | Socket-outlet                              | Description   | 2P+E - 16A                     |
| Colour   | Ivory                                      | Voltage   | 250 V ac                       |
| Standard   | German                                     | Characteristics   | With safety shields            |
| For plug pins  | Ø 4.8 mm                                   | Wiring terminals  | With screw                     |
| Standard   | IEC 60884-1; DIN VDE 0620-1; UNE 20315-1-1 | Resistance at test voltage                                      | 2000 V at 50 Hz for 1 minute   |
| Insulation resistance  | > 5 MOhm                                   | Prolonged operation socket (no.of position changes)             | 10.000 at In 250 V ac cosØ=0,8 |
| Thermo-pressure with ball                                    | 125 °C                                     | Glow Wire Test  | 850 °C                         |
| Terminal grip on cable traction                              | > 50 N                                     | Terminal tightening capacity stranded cables (mm <sup>2</sup> ) | min. 0,75 - max. 2x4           |
| Terminal tightening capacity solid cables (mm <sup>2</sup> ) | min. 0,5 - max. 2x2,5                      | No. modules   | 2                              |
| Material   | Technopolymer                              |   |                                |

### DIMENSIONAL



### TECHNICAL SYMBOLOGY



### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 20/04/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice