


PRODUCT-DETAILS

DDA802A-100/0.03 APR

DDA802A-100/0.03 APR Residual Current Device Block



Informations générales

Extension du type de produit	DDA802A-100/0.03 APR
Code de produit	2CSB802401R1000
EAN	8012542544630
Description courte	DDA802A-100/0.03 APR Residual Current Device Block
Description longue	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings. It is suitable for assembly with MCBs S800 series up to 100A.

Technique

Normes et standards	IEC EN 60947-2 Ann. B
Type of Residual Current	A type
Adapté pour	S800S S800N S800C S800B
Tension nominale (U_r)	230 V AC 240 V AC 400 V AC
Tension	400/690 V

Tension assignée d'isolement (U_i)	690 V
Tension assignée de tenue aux chocs (U_{imp})	6 kV
Courant nominal (I_n)	100 A
Rated Residual Current	30 mA
Maximum Surge Current	3 kA
Leakage Current Type	A
Fréquence assignée (f)	50 ... 60 Hz
Power Loss	7 W
Nombre de pôles	2
Operating Characteristic	Instantaneous (APR High Immunity)
Options Provided	-
Connecting Capacity	Rigid 6 ... 50 mm ² Flexible 6 ... 70 mm ²

Environnement

Température extérieure	-25...60 °C
Température de l'air ambiant	Operation -25...60 °C
Indice de protection	IP2X
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	9AKK106713A5616
REACH Declaration	9AKK108467A9482
Informations environnementales	refer to RoHS information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Technique UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 ... 0.03 A
-------------------------------------	-----------------

Dimensions

Width in Number of Modular Spacings	4.5
Produit Largeur Net	81 mm
Produit Hauteur Net	108.2 mm
Produit Longueur Net	82.3 mm
Poids net	0.300 kg

Commande

Quantité minimum	1 pièce
------------------	---------

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Poids	0.4 kg

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	9AKK106713A5616
-----------------------------------	-----------------

Installation

Instructions et manuels	2CSB427001D0003
-------------------------	-----------------

Popular Downloads

Fiche produit, informations techniques	2CSC400002D0209
---	-----------------

Classifications

ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Business
CN8	85363030
eClass	V11.0 : 27142210
Code de classification d'objet	F

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → High Performance Circuit Breakers HPCBs → Accessoires pour Disjoncteurs ≤125A

