


PRODUCT-DETAILS

TB/U2.5.1-CG

TB/U2.5.1-CG Control element 2g.



Informations générales

Extension du type de produit	TB/U2.5.1-CG
Code de produit	2CKA006300A1540
EAN	4011395230749
Description courte	TB/U2.5.1-CG Control element 2g.

Description longue	<p>Ordering possible only in connection with the design ID. The icons and/or texts are configured by means of a web configuration tool. Freely configurable multifunction control element. With integrated KNX bus coupler. With integrated temperature sensor. With integrated proximity function. Push switch function: switching / dimming / blind / sending values / scenes etc. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. The bus connection is provided via the enclosed bus terminal. Number of bus subscribers: 1</p>
--------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Installation

Instructions et manuels	No document needed
-------------------------	--------------------

Technique

Fiche produit, informations techniques	No document needed
----------------------------------------	--------------------

Number of Buttons	2
Number of Actuation Points	2
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Design Range	tacteo
Type de montage	Surface Mounted
Finition de surface	Surface protection: Untreated Surface finishing: Glossy
Matériau	Glass
Couleur	other
Nombre de batteries	0
Application Function	Blind / Shutter / Shading Control Electrical Load and Light Control Room Climate Control

Environnement

Température de l'air ambiant	Operation -5 ... +45 °C
Indice de protection	IP20
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations RoHS	2CKA200000E5452
REACH Declaration	2CKA309999E9999

Dimensions

Poids net	103.4 g
Profondeur d'encastrement (t ₂)	35 mm

Commande

Quantité minimum	1 pièce
Emballage Niveau 1 Unités	carton 1 pièce
Emballage Niveau 1 Poids	0.209 kg
Code douanier	85365080
E-Number (Finland)	2814639
E-Number (Sweden)	1739651
Pays d'origine	Germany (DE)

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CKA100000E2525
--------------------------------	-----------------

Classifications

ETIM 8	EC000672 - Touch sensor for bus system
ETIM 9	EC000672 - Touch sensor for bus system
Catégorie DEEE	5. Small Equipment (No External Dimension More Than 50 cm)
DEEE B2C / B2B	Business To Consumer
CN8	8536 50 80
eClass	V11.0 : 27143138

Catégories

Produits basse tension → Home and Building Automation → KNX → User Operation → ABB tacteo® → 2 fold

