

PRODUCT-DETAILS

AFC09-30-10K-84

AFC09-30-10K-84 110V50Hz 110-120V60Hz

Contacteur



Algemene informatie

Type	AFC09-30-10K-84
Artikelnummer	1SBL131005R8410
EAN	3471523013971
Omschrijving	AFC09-30-10K-84 110V50Hz 110-120V60Hz Contacteur

Omschrijving	The AFC09-30-10K-84 is a 3-pole - 690 V IEC or 600 V UL contactor with 1 N.O built-in auxiliary contact and Push-in terminals, mainly controlling power circuits up to 4 kW / 400 V AC (AC-3) or 5 hp / 480 V AC UL and 25 A (AC-1) or 25 A UL general use. Within the AF platform, AFC contactors offer an optimized operating time for AC controlled applications with electromagnetic coil (control voltage : 110 V AC 50 Hz / 110 ... 120 V AC 60 Hz). AFC contactors have a block type design and can be easily extended with add-on auxiliary contact blocks and a wide range of additional accessories.
--------------	--

Ordering

Minimale bestelhoeveelheid	1 stuk
Numerus douanetarief	85364900

Popular Downloads

Gegevensblad, technische	1SBC100219C0201
--------------------------	-----------------

informatie

Instructies en handleidingen	1SBC101061M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product netto breedte	45 mm
Product netto diepte	77 mm
Product netto hoogte	92.3 mm
Product netto gewicht	0.314 kg

Technical

Aantal hoofdcontacten NO	3
Aantal hoofdcontacten NC	0
Aantal hulpcontacten NO	1
Aantal hulpcontacten NC	0
Normen	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1
Nominaal bedrijfsvoltage	Auxiliary Circuit 690 V Main Circuit 690 V
Toegekende frequentie (f)	Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventionele vrije-lucht thermische stroom (I_{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40^\circ\text{C}$ 35 A acc. to IEC 60947-5-1, $\Theta = 40^\circ\text{C}$ 16 A
Nominale bedrijfsstroom AC-1 (I_e)	(690 V) 40 °C 25 A (690 V) 60 °C 25 A (690 V) 70 °C 22 A
Nominale bedrijfsstroom AC-3 (I_e)	(415 V) 60 °C 9 A (440 V) 60 °C 9 A (500 V) 60 °C 9.5 A (690 V) 60 °C 7 A (380 / 400 V) 60 °C 9 A (220 / 230 / 240 V) 60 °C 9 A
Nominale bedrijfsstroom AC-3e (I_e)	(415 V) 60 °C 9 A (440 V) 60 °C 9 A (500 V) 60 °C 9.5 A (690 V) 60 °C 7 A (380 / 400 V) 60 °C 9 A (220 / 230 / 240 V) 60 °C 9 A
Nominale bedrijfsvermogen AC-3 (P_e)	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
Nominale bedrijfsvermogen AC-3e (P_e)	(415 V) 4 kW (440 V) 4 kW (500 V) 5.5 kW (690 V) 5.5 kW (380 / 400 V) 4 kW (220 / 230 / 240 V) 2.2 kW
Nominale bedrijfsstroom AC-15 (I_e)	(500 V) 2 A (690 V) 2 A

(24 / 127 V) 6 A
 (220 / 240 V) 4 A
 (400 / 440 V) 3 A

Nominale kortstondige grensstrom (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximale breekcapaciteit	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 106 A
Maximale elektrische schakelfrequentie	(AC-1) 600 omwentelingen per uur (AC-15) 1200 omwentelingen per uur (AC-2 / AC-4) 300 omwentelingen per uur (AC-3) 1200 omwentelingen per uur (DC-13) 900 omwentelingen per uur
Nominale bedrijfsstroom DC-1 (I_e)	(110 V) 1-Pole, 40 °C 10 A (110 V) 1-Pole, 60 °C 10 A (110 V) 1-Pole, 70 °C 10 A (110 V) 2 Poles in Series, 40 °C 25 A (110 V) 2 Poles in Series, 60 °C 25 A (110 V) 2 Poles in Series, 70 °C 22 A (110 V) 3 Poles in Series, 40 °C 25 A (110 V) 3 Poles in Series, 60 °C 25 A (110 V) 3 Poles in Series, 70 °C 22 A (220 V) 2 Poles in Series, 40 °C 10 A (220 V) 2 Poles in Series, 60 °C 10 A (220 V) 2 Poles in Series, 70 °C 10 A (220 V) 3 Poles in Series, 40 °C 25 A (220 V) 3 Poles in Series, 60 °C 25 A (220 V) 3 Poles in Series, 70 °C 22 A (72 V) 1-Pole, 40 °C 25 A (72 V) 1-Pole, 60 °C 25 A (72 V) 1-Pole, 70 °C 22 A (72 V) 2 Poles in Series, 40 °C 25 A (72 V) 2 Poles in Series, 60 °C 25 A (72 V) 2 Poles in Series, 70 °C 22 A (72 V) 3 Poles in Series, 40 °C 25 A (72 V) 3 Poles in Series, 60 °C 25 A (72 V) 3 Poles in Series, 70 °C 22 A
Nominale bedrijfsstroom DC-3 (I_e)	(110 V) 1-Pole, 40 °C 6 A (110 V) 1-Pole, 60 °C 6 A (110 V) 1-Pole, 70 °C 6 A (110 V) 2 Poles in Series, 40 °C 25 A (110 V) 2 Poles in Series, 60 °C 25 A (110 V) 2 Poles in Series, 70 °C 22 A (110 V) 3 Poles in Series, 40 °C 25 A (110 V) 3 Poles in Series, 60 °C 25 A (110 V) 3 Poles in Series, 70 °C 22 A (220 V) 2 Poles in Series, 40 °C 6 A (220 V) 2 Poles in Series, 60 °C 6 A (220 V) 2 Poles in Series, 70 °C 6 A (220 V) 3 Poles in Series, 40 °C 25 A (220 V) 3 Poles in Series, 60 °C 25 A (220 V) 3 Poles in Series, 70 °C 22 A (72 V) 1-Pole, 40 °C 25 A (72 V) 1-Pole, 60 °C 25 A (72 V) 1-Pole, 70 °C 22 A (72 V) 2 Poles in Series, 40 °C 25 A (72 V) 2 Poles in Series, 60 °C 25 A (72 V) 2 Poles in Series, 70 °C 22 A (72 V) 3 Poles in Series, 40 °C 25 A (72 V) 3 Poles in Series, 60 °C 25 A (72 V) 3 Poles in Series, 70 °C 22 A
Nominale bedrijfsstroom DC-5 (I_e)	(110 V) 1-Pole, 40 °C 4 A (110 V) 1-Pole, 60 °C 4 A

	(110 V) 1-Pole, 70 °C 4 A (110 V) 2 Poles in Series, 40 °C 10 A (110 V) 2 Poles in Series, 60 °C 10 A (110 V) 2 Poles in Series, 70 °C 10 A (110 V) 3 Poles in Series, 40 °C 25 A (110 V) 3 Poles in Series, 60 °C 25 A (110 V) 3 Poles in Series, 70 °C 22 A (220 V) 2 Poles in Series, 40 °C 4 A (220 V) 2 Poles in Series, 60 °C 4 A (220 V) 2 Poles in Series, 70 °C 4 A (220 V) 3 Poles in Series, 40 °C 9 A (220 V) 3 Poles in Series, 60 °C 9 A (220 V) 3 Poles in Series, 70 °C 9 A (72 V) 1-Pole, 40 °C 9 A (72 V) 1-Pole, 60 °C 9 A (72 V) 1-Pole, 70 °C 9 A (72 V) 2 Poles in Series, 40 °C 25 A (72 V) 2 Poles in Series, 60 °C 25 A (72 V) 2 Poles in Series, 70 °C 22 A (72 V) 3 Poles in Series, 40 °C 25 A (72 V) 3 Poles in Series, 60 °C 25 A (72 V) 3 Poles in Series, 70 °C 22 A
Nominale bedrijfsstroom DC-13 (I_e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Nominaal isolatievoltage (U_i)	acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Nominale impuls grensvoltage (U_{imp})	6 kV
Maximale mechanische schakelfrequentie	3600 omwentelingen per uur
Nominale stuurstroomkringspanning (U_c)	50 Hz 110 V 60 Hz 110 ... 120 V
Bedieningstijd	Between Coil De-energization and NC Contact Closing 9 ... 20 ms Between Coil De-energization and NO Contact Opening 4 ... 18 ms Between Coil Energization and NC Contact Opening 7 ... 21 ms Between Coil Energization and NO Contact Closing 10 ... 26 ms
Montage op DIN-rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Montage door schroeven (niet meegeleverd)	2 x M4 screws placed diagonally
Verbindingscapaciteit hoofdcircuit	Flexible with Ferrule 1/2x 0.5 ... 4 mm ² Flexible with Insulated Ferrule 1x 0.5 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 2.5 mm ² Flexible 1/2x 0.5 ... 4 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 4 ... 6 mm ²
Verbindingscapaciteit hulpcircuit	Flexible with Ferrule 1/2x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm ² Flexible 1/2x 0.5 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ²
Verbindingscapaciteit controlecircuit	Flexible with Ferrule 1/2x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm ² Flexible 1/2x 0.5 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ²

Kabelstriplengte	Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm
Beschermingsgraad	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Terminaaltype	Push-in Spring Terminals

Technical UL/CSA

NEMA-grootte	00
Continuous Current Rating NEMA	9 A
Horsepower Rating NEMA	(115 V AC) Single Phase 1/3 Hp (200 V AC) Three Phase 1-1/2 Hp (230 V AC) Single Phase 1 Hp (230 V AC) Three Phase 1-1/2 Hp (460 V AC) Three Phase 2 Hp (575 V AC) Three Phase 2 Hp
Maximale bedrijfsspanning UL/CSA	Main Circuit 600 V
Algemeen gebruik klasse UL/CSA	(600 V AC) 25 A
Paardenkrachtklasse UL/CSA	(120 V AC) Single Phase 3/4 hp (200 ... 208 V AC) Three Phase 2 hp (220 ... 240 V AC) Three Phase 2 hp (240 V AC) Single Phase 1-1/2 hp (440 ... 480 V AC) Three Phase 5 hp (550 ... 600 V AC) Three Phase 7-1/2 hp
Verbindingscapaciteit hoofdcircuit UL/CSA	Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-10 AWG
Verbindingscapaciteit hulpcircuit UL/CSA	Rigid Solid 1/2x 18-14 AWG
Verbindingscapaciteit controlecircuit UL/CSA	Rigid Solid 1/2x 18-14 AWG

Environmental

Omgevingsluchttemperatuur	bij schakelaar zonder thermisch overbelastingsrelais -40 ... 70 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 60 °C Close to Contactor without Thermal O/L Relay (Uc) -40 ... 70 °C bij schakelaar voor opslag -60 ... +80 °C
Klimaatbestendig	Category B according to IEC 60947-1 Annex Q
Maximale werkhoogte toegestaan	Without Derating 3000 m
Weerstand tegen trillingen volgens IEC 60068-2-6	5 ... 300 Hz 4 g closed position / 2 g open position

Certificates and Declarations

BV-certificaat	BV_2634H24898C0
CB-certificaat	CB_SE-108891
CQC-certificaat	CQC2010010304445624
Declaration of Conformity - CCC	2020980304001253

Conformiteitsverklaring - CE	1SBD250024U1000
Declaration of Conformity - UKCA	1SBD250045U1000
UL-certificaat	UL-US-2150887-5 UL-CA-2142658-5

Container Information

Pakketniveau 1 Units	doos 1 stuk
Pakketniveau 1 Breedte	93 mm
Pakketniveau 1 Lengte	86 mm
Pakketniveau 1 Hoogte	45 mm
Pakketniveau 1 Bruto gewicht	0.314 kg
Pakketniveau 1 EAN	3471523013971
Pakketniveau 3 Units	1080 stuk

Classifications

Object classificatiecode	Q
ETIM 6	EC000066 - Magneetschakelaar
ETIM 7	EC000066 - Power contactor, AC switching
ETIM 8	EC000066 - Magneetschakelaar
eClass	V11.0 : 27371003
UNSPSC	39121529
IGCC (IDEA granulaire categoriecode)	4755 >> Contactors

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Magneetschakelaars → Magneetschakelaars

