

PRODUCT-DETAILS

## TY37MX

## CABLE TIE 120LB 14IN BLK NYL MT HOL



General Information	
Extended Product Type	TY37MX
Product ID	7TAG009520R0060
EAN	5414363064381
Catalog Description	CABLE TIE 120LB 14IN BLK NYL MT HOL
Long Description	Integrated Mounting Hole Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to 105 Degrees Celsius (220 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, Length of 356mm (14 Inches), Width of 7.6mm (0.3 Inches), Thickness of 2mm (0.08 Inches), Tensile Strength Rating of 534 Newtons (120 pounds), 1/4-Inch Mounting Hole, Bulk Pack
Ordering	
EAN	5414363064381
UPC	786210824956
Country of Origin	United States (US)
Selling Unit of Measure	<u>each</u>
Dimensions	
Product Net Width	0.301 in 7.65 mm
Product Net Depth / Lenath	14 in 356 mm

TY37MX 2

Package Level 1 Units	500 piece
Package Level 2 Units	1000 piece
Package Level 2 Width	20.6 ir 523 mm
Package Level 2 Height	10 ir 254 mm
Package Level 2 Depth / Length	20 ir 508 mm
Technical UL/CSA	
Flammability According to	V-2

Additional Information	
Brand / Label	Ty-Rap
Bundle Diameter	0.236 to 3.54 in 6 to 90 mm
Color	Black
Effective Date	19671113
Lock Type	Stainless Steel Barb
Material	Nylon/Polyamide 6.6
Product Name	NYLON CABLE TIES AND ACCESSORIES
Product Type	Integrated Mounting Hole
RoHS Date	9AKK107991A8069
Special Functions	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Tensile Strength	120 lb 534 N
Thickness	0.08 in 2 mm

Certificates and Declarations	
Data Sheet, Technical	TDS000577

Classifications	
ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
ETIM 8	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5044 >> Mounted Head Ties

## Categories

TY37MX 3

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

