



Screw

terminal block 10mm² portafusibile, 1-level, with CIL predisposition, beige.color



| | |
|---|--|
| Series | FPC – FPL |
| Code | FP300 |
| Type | FPL.10/C |
| HS code | 85369010 |
| Colour | Beige |
| TECHNICAL FEATURES | |
| Function/Type | Fuse-holder 6.3×32 with alarm (1) |
| Rated cross-section | 10 mm ² |
| Connecting capacity | |
| Flexible wire | 1.5-16 mm ² |
| Rigid wire | 1.5-16 mm ² |
| Wire with ferrule - ferrule type | 10 mm ² – WP100/21 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 800 V |
| Maximum current (rated cross-section) | 10 A |
| Caliber | B6 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 300 V |
| Maximum current (rated cross-section) | 15 A |
| Section (min-max) | 20-6 (AWG) |
| Tightening torque value (UL) | 7 lb.in |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Rated impulse withstand voltage / pollution degree | 6 kV / 3 (2) |
| Insulation stripping length | 17 mm |
| Tightening torque value (nom. / max.) | 1.2 / 1.9 Nm |
| Width (pitch) | 12 mm |
| Length | 63 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 71 / 79 / 75 mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | - |
| Blue | - |
| Beige | - |
| Thickness | - |
| Cross-connection | |
| Model A) | - |
| Model B) | - |
| Rated current carrying capacity IEC/ATEX | - |
| Cross-connection identification strip | - |
| Coloured partition plate | DFU/6/R (cod. DU06R) |
| Cross-connection barrier | - |
| Test plug socket | - |
| Test plug | - |
| Connection knob | MSM (cod. FC103) (3) |
| Marking | |
| Snap-on numbering strip | CNU/8/51 (cod. NU0851S) – CNU/10/61 (cod. NU1061S) |
| Single marking tag | - |
| Fuse type | 6.3×32 mm (1) |
| Conductive element | SFC/CO (cod. FC102) |
| Light alarm circuit (12...48 V) | - |
| Light alarm circuit (110...230 V) | CIL/115-230 (cod. SF510) |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| IEC 60715/TH35 | PR/3/... |
| IEC 60715/G32 | - |
| APPROVALS AND MARKINGS | |
| | |



* Suitable for 6.3x32 mm fuses* Accessory with alarm LED, available separately* End section plate is not required
1 For more details on accessories, refer to the relevant chapters2 (1) Value referred to the insulation characteristics of the terminal blocks3 (2) An optional light alarm is available4 (3) Mounted on the levers, it allows simultaneous disconnection of up to 6 terminals blocks

DESCRIZIONE DEL PRODOTTO

FPL.10/C Screw terminal block 10mm² portafusibile, 1-level, with CIL predisposition, beige.color