



Spring-clamp terminal block 10mm2, 1-level, blue color

| | |
|---|---|
| Series | HMM |
| Code | HI330 |
| Type | HMM.10 (Ex)i |
| HS code | 85369010 |
| Colour | blue |
| TECHNICAL FEATURES | |
| Function/Type | Feed-through |
| Rated cross-section | 10 mm ² |
| Connecting capacity | |
| Flexible wire | 1.5-16 mm ² |
| Rigid wire | 1.5-16 mm ² |
| Wire with ferrule - ferrule type | 10 mm ² – WP100/21 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 1000 V |
| Maximum current (rated cross-section) | 57 A |
| Caliber | A6 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 57 A |
| Section (min-max) | 20-6 (AWG) |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | 500 V |
| Maximum current (rated cross-section) | 57 A |
| Operating temperature Min/Max | -40 °C / +80 °C |
| Rated impulse withstand voltage / pollution degree | 8 kV / 3 |
| Insulation stripping length | 18 mm |
| Width (pitch) | 10 mm |
| Length | 71 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 53 / 61 / – mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | HMT.10/PT/GR (cod. HM331GR) |
| Blue | HMT.10/PT (Ex)i (cod. HI331) |
| Thickness | 1.5 mm |
| Cross-connection | |
| Model A) | PTC/11/... (cod. PTC11...) |
| Model B) | – |
| Rated current carrying capacity IEC/ATEX | |
| Cross-connection identification strip | – |
| Coloured partition plate | DFH/4/R (cod. DH04R) |
| Cross-connection barrier | – |
| Test plug | SDD/1 (cod. DD001) |
| Modular test plug | – |
| End section for modular test plug | – |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) |
| Single marking tag for pitch insertion | – |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| DIN rail according to IEC 60715/TH35 | PR/3/.. |
| APPROVALS AND MARKINGS |  |



1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

HMM.10(EX)
Sping-clamp terminal block 10mm², 1-level, blue color