

# BRANTA METALICA

WQJP06882

LED luminaire BRANTA METALICA, with a power of 19 W, high light efficacy 140 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 36° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



|                    |               |                           |              |
|--------------------|---------------|---------------------------|--------------|
| Power              | <b>19 W</b>   | Voltage                   | <b>230 V</b> |
| Colour temperature | <b>3000 K</b> | Colour of light           | <b>WW</b>    |
| Beam angle         | <b>36 °</b>   | Degree of protection (IP) | <b>IP20</b>  |


## Technical data

|                              |                   |
|------------------------------|-------------------|
| Code                         | WQJP06882         |
| Power                        | 19 W              |
| Nominal current              | 90.9 mA           |
| Voltage                      | 230 V             |
| Energy consumption           | 19 kWh/1000h      |
| Frequency                    | 50HZ Hz           |
| Protection class             | I                 |
| Power supply included        | +                 |
| Manufacturer of power supply | TCI               |
| Power factor                 | 0.93              |
| Useful luminous flux*        | 2660 lm (360°)    |
| Luminous flux**              | 1710 lm (360°)    |
| Lamp efficacy                | 140 lm/W          |
| Colour temperature           | 3000 K            |
| Colour of light              | WW                |
| Beam angle                   | 36 °              |
| RA                           | 80                |
| Light source included        | +                 |
| Producer of LED diodes       | CREE              |
| Uniformity of color SDCM max | 3                 |
| Dimmable                     | DALI              |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 50000 h           |
| Housing material             | Aluminum          |
| Degree of protection (IP)    | IP20              |
| Colour                       | Black             |
| Dimension (AxBxC)            | 90x200x165 mm     |
| For use                      | Inside            |
| Assembly method              | on track          |
| Application                  | Inside            |
| Made in                      | PL                |
| Other                        | L90B10 - 73000h , |



## Related documents



 Photometric file