

ALLDAY BASIC CCT

SLI047302CCT_PW

LED luminaire ALLDAY BASIC CCT with the possibility of changing the light color (CCT), with a power of 50 W, high light efficacy 125 lm/W. Thanks to the ability to change the color temperature (CCT) in the range from 3000K to 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. Suitable for both surface and suspended mounting.




Power	50 W	Voltage	230 V
Luminous flux*	6250 lm (360°)	Colour temperature	2700/4000/6000 K
Colour of light	CCT	Beam angle	115 °
Degree of protection (IP)	IP20		

Technical data


Code	SLI047302CCT_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	6250 lm (360°)
Luminous flux**	5000 lm (360°)
Lamp efficacy	125 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	115 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	1503x42x37 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Made in	PL
Other	Light color change function 2700K/4000K/6000K ,

Related documents



 User manual



 Declaration of Conformity



 Photometric file

