

APJ OD OG 60 (787 357)



Figure without obligation

| Type | APJ OD OG 60 |
|--|--|
| Part No. | 787 357 NEW |
| Arc fault protection class (box test 7 kA / 0.5 s – single-pole) | APC 2 |
| Arc energy (W_{arc} or W_{LBP}) | 320 kJ |
| Arc rating – ATPV (open arc) | 16 cal / cm ² *) |
| Arc rating – ELIM (open arc) | 13 cal / cm ² |
| PPE category (NFPA 70E) | PPE 2 |
| Material | Modacrylic (40%), viscose (59%), static inhibitors (1%), PU membrane: meta-armid knitting (100%) |
| Weight per unit area | 300 g/m ² |
| Material (sewing thread) | Kevlar (100%) |
| Standard | IEC 61482-2, EN ISO 11612, EN 1149-5, EN ISO 20471, EN 13034, EN ISO 13688, EN ISO 11611 |
| Primary colour | fluorescent orange |
| Secondary colour | grey |
| Zipper | red |
| Size (international) | 60 (2XL) |
| Design code | JOORGRE0000P0000 |
| Weight | 932 g |
| Customs tariff number | 62033911 |
| GTIN | 4013364478237 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.