

## PRODUCT DATASHEET

### LED Classic A 75 10W 840 Frosted E27

BELLALUX® CLA | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Shockproof and vibration-proof thanks to LED technology
- No UV radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

#### Product features

- LED lamps for line voltage
- Not dimmable
- Mercury-free lamps




TECHNICAL DATA

Electrical data

|  |             |
|--|-------------|
| Nominal wattage                        | 10 W        |
| Construction wattage                   | 10.00 W     |
| Nominal voltage                        | 220...240 V |
| Operating mode                         | AC Mains    |
| Claimed equiv. conventional lamp power | 75 W        |
| Nominal current                        | 70 mA       |
| Type of current                        | AC          |
| Inrush current                         | 4.2 A       |
| Operating frequency                    | 50...60 Hz  |
| Mains frequency                        | 50...60 Hz  |
| Max. lamp number on MCB B10 A          | 219         |
| Max. lamp number on MCB B16 A          | 229         |
| Total harmonic distortion              | 111.70 %    |
| Power factor $\lambda$                 | 0.65        |

Photometrical data

|   |            |
|---|------------|
| Luminous flux                           | 1055 lm    |
| Luminous efficacy                       | 105 lm/W   |
| Lumen main.fact.at end of nom.life time | 0.93       |
| Light color (designation)               | Cool White |
| Color temperature                       | 4000 K     |
| Color rendering index Ra                | 80         |
| Light color                             | 840        |
| Standard deviation of color matching    | ≤6 sdcn    |
| Flickering metric (Pst LM)              | 1.0        |
| Stroboscope effect metric (SVM)         | 0.4        |



EPREL Data Spectral Diagram LEDr  
\_4000K

## Light technical data

|                     |          |
|---------------------|----------|
| Beam angle          | 150 °    |
| Warm-up time (60 %) | < 0.50 s |
| Starting time       | < 0.5 s  |

## Dimensions &amp; Weight

|                  |           |
|------------------|-----------|
| Overall length   | 109.00 mm |
| Diameter         | 60.00 mm  |
| Maximum diameter | 60 mm     |
| Product weight   | 26.00 g   |

## Temperatures &amp; operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+40 °C |
| Maximum temperature at tc test point | 100 °C       |

## Lifespan

|  |         |
|--|---------|
| Lifespan L70/B50 at 25 °C                    | 15000 h |
| Number of switching cycles                   | 100000  |
| Lumen maintenance at end of service lifetime | 0.93    |

## Additional product data

|                             |  |
|-----------------------------|--|
| Base (standard designation) | E27  |
| Mercury content             | 0.0 mg   |
| Mercury-free                | Yes  |
| Design / version            | Frosted  |
| Product remark              | All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value |

## Capabilities

|          |    |
|----------|----|
| Dimmable | No |
|----------|----|

### Certificates & Standards

|  |                 |
|--|-----------------|
| Energy efficiency class                      | F 1)            |
| Energy consumption                           | 10.00 kWh/1000h |
| Type of protection                           | IP20            |
| Standards                                    | CE / UKCA / EAC |
| Photobiological safety group acc. to EN62778 | RG1             |

1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

### Country-specific categorizations

|                 |                             |
|-----------------|-----------------------------|
| ILCOS           | DRAA/F-9/840-220-240-E27-60 |
| Order reference | LED CLA75 10W/8             |

### LOGISTICAL DATA

|                              |              |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

### Energy labelling regulation data acc EU 2019/2015





|   |              |
|---|--------------|
| Lighting technology used                            | LED          |
| Non-directional or directional                      | NDLS         |
| Mains or non-mains                                  | MLS          |
| Light source cap-type (or other electric interface) | E27          |
| Connected light source (CLS)                        | No           |
| Color-tuneable light source                         | No           |
| Envelope  | No           |
| High luminance light source                         | No           |
| Anti-glare shield                                   | No           |
| Correlated colour temperature type                  | SINGLE_VALUE |
| Standby power                                       | 0.00 W       |
| Claim of equivalent power                           | Yes          |
| Length  | 109.00 mm    |
| Height  | 60.00 mm     |
| Width   | 60.00 mm     |
| Chromaticity coordinate x                           | 0.382        |
| Chromaticity coordinate y                           | 0.380        |
| R9 Colour rendering index                           | 8            |
| Beam angle correspondence                           | SPHERE_360   |

|                     |                                |
|---------------------|--------------------------------|
| Survival factor     | 0.90                           |
| Displacement factor | 0.905                          |
| EPREL ID            | 1403214,523313,1351505,1857050 |
| Model number        | AC31155,AC55987                |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

### DOWNLOAD DATA

| Documents and certificates  |                                 | Document name                           |
|---|---------------------------------|---|
|     | Declarations of conformity      | Classic A_B_P 15000h FR                 |
|     | Declarations of conformity      | LED CLASSIC A_P NON-DIM                 |
|    | Declarations of conformity UKCA | LED CLASSIC A_P NON-DIM                 |
| Photometric and lighting design files   |                                 | Document name                           |
|  | Spectral power distribution     | EPREL Data Spectral Diagram LEDr _4000K |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075128125 | Folding box<br>1             | 60 mm x 60 mm x 145 mm               | 39.00 g      | 0.52 dm <sup>3</sup> |
| 4058075128132 | Shipping box<br>10           | 323 mm x 135 mm x 136 mm             | 836.00 g     | 5.93 dm <sup>3</sup> |
| 4058075589629 | Shipping box<br>6            | 202 mm x 134 mm x 120 mm             | 332.00 g     | 3.25 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

