

PRODUCT DATASHEET

HAL CL A ES 70 W 127 V E27

HALOGEN CLASSIC A | Halogen lamps, classic bulb shape



Areas of application

- General illumination
- Mood lighting
- Entrance lighting
- Restaurants, hotels and similar prestigious applications

Product benefits

- Simple direct replacement for conventional incandescent lamps
- The same pleasant quality of light as that of an incandescent lamp
- Instant 100 % light, no warm-up time
- Contains no mercury
- UV filter

Product features

- 100 % dimmable
- Perfect color rendering ($R_a: 100$)
- Average life: 2,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	70 W
Construction wattage	70.00 W
Nominal voltage	127 V
Power factor λ	1.00

Photometrical data

Color rendering index Ra	100
Light color	10

Light technical data

Starting time	0 s
---------------	-----

Dimensions & Weight

Overall length	97.00 mm
Light center length (LCL)	73,0 mm
Diameter	55.00 mm
Product weight	25.00 g

Additional product data

Base (standard designation)	E27
Mercury-free	Yes
Design / version	Bulb

Capabilities

Burning position	Any
------------------	-----

Country-specific categorizations

ILCOS	HSGSA/C/UB-70-127-E27
Order reference	64547 A ES 70W

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	94.00 mm
Height	55.00 mm
Width	55.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899030695	Folding box 1	56 mm x 56 mm x 97 mm	34.00 g	0.30 dm ³
4052899091870	Bundle 10	280 mm x 112 mm x 97 mm	340.00 g	3.04 dm ³
4052899091887	Shipping box 50	570 mm x 294 mm x 109 mm	1984.00 g	18.27 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.