

PRODUCT-DETAILS

LD38-4

LD38-4 Additional Terminal Block



Algemene informatie

Type	LD38-4
Artikelnummer	1SBN072308R1000
EAN	3471523130838
Omschrijving	LD38-4 Additional Terminal Block
Omschrijving	LD38-4 is an additional terminal block designed to increase the connecting capacity of 3-pole AF(C)(S)26 ... 38 contactors on which it is fitted and for preparation of the wiring before final connection to the contactor. LD38-4 blocks is 3-pole terminal block with tunnel terminals.

Ordering

Minimale bestelhoeveelheid	2 stuk
Numer douanetarief	85369010
Product hoofdtype	Accessories for Block Contactors

Popular Downloads

CAD Dimensional Drawing	2CDC001079B0201
-------------------------	-----------------

Dimensions

Product netto breedte	44.8 mm
Product netto diepte	50 mm
Product netto hoogte	40.5 mm
Product netto gewicht	0.07 kg

Technical

Verbindingscapaciteit hoofdcircuit	Flexible with Ferrule 1x 2.5 ... 16 mm ² Flexible with Ferrule 1/1x 2.5 ...10/...16 mm ² Flexible with Insulated Ferrule 1x 2.5 ... 16 mm ² Flexible with Insulated Ferrule 1/1x 2.5 ...10/...16 mm ² Rigid Solid 1/2x 2.5 ... 4 mm ² Rigid Stranded 1/1x 6 ...16/ ... 25 mm ²
Aansluitklemmen (geleverd in open positie) Hoofdpolen	M5 with 2 x (7 width x 5.8/9.2 depth) double connector
Verontreinigingsgraad	3
Toegekende frequentie (f)	Main Circuit 50 / 60 Hz
Nominaal isolatievoltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Aanbevolen schroevendraaier	Main Circuit Slot Main Circuit 6.5 Main Circuit Pozidriv 2
Normen	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1
Geschikt voor	AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC26 AFC30 AFC38
Terminaltype	Schroef
Aanhaalmoment	Main Circuit 2.5 N·m
Kabelstriplengte	Main Circuit 14 mm

Technical UL/CSA

Verbindingscapaciteit hoofdcircuit UL/CSA	1x 8-4 AWG 2x 8-6 AWG
Aanhaalmoment UL/CSA	Main Circuit 22 in-lb

Environmental

Beschermingsgraad	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
RoHS-informatie	2CMT2021-006277
AEEA B2C / B2B	Business To Business
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Conformiteitsverklaring - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000

GOST-certificaat	GOST_POCCFR.ME77.B07175.pdf
UL-certificaat	UL-US-2150887-5 UL-CA-2142658-5

Container Information

Pakketniveau 1 Units	tas 2 stuk
Pakketniveau 1 Breedte	90 mm
Pakketniveau 1 Lengte	160 mm
Pakketniveau 1 Hoogte	46 mm
Pakketniveau 1 Brutogewicht	0.14 kg
Pakketniveau 1 EAN	3471523130838

Classifications

eClass	V11.1 : 27371392
E-Number (Sweden)	3210256
ETIM 6	EC002498 - Toebehoren voor laagspannings-schakeltechniek
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Toebehoren/onderdelen voor laagspannings-schakeltechniek
ETIM 9	EC002498 - Toebehoren/onderdelen voor laagspannings-schakeltechniek
IGCC (IDEA granulaire categoriecodel)	4547 >> Terminal blocks
UNSPSC	39121410

Categorieën

Laagspanningsproducten en -systemen → Control Producten → Magneetschakelaars → Magneetschakelaar toebehoren

