


1
electromechanical relay 24Vac 4PDT 6A, screw, pluggable

Code	XCM4A024
Type	CM4A024
Series	CM
Connection terminal	2.5 mm ² screw
Input channels	1 pluggable
Contact type	4PDT, 4 form C, AgNi
Nominal current	6 A (240 Vac)
Continuous current	12 A
Min applicable load	10 mA / 12 V
Operating temperature range	-20...+60°C
Input / output isolation	2.5 kVac / 60 s
Protection degree	IP 20
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	27x75x68 mm
Approximate weight	54 g
Mounting information	on a rail, side by side
APPROVALS AND MARKINGS	CE
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
Marking tag	already mounted
Plugin jumper	CMB27B (6 poles)
Input rated voltage	24 Vac ±10%
Spare part relay	804033



DESCRIZIONE DEL PRODOTTO

CM4A024 1 electromechanical relay 24Vac 4PDT 6A, screw, pluggable