



# CoreLine Wall-mounted

## WL140V LED12S/830 PSU WH

- Power supply unit (ON/OFF) - Symmetrical - 120° x 120°

CoreLine wall-mounted solutions deliver on the CoreLine promise of innovative, easy-to-install and high quality luminaires. These circular-shaped, surface-mounted luminaires are suitable for both ceiling and wall installations and are easy to apply in circulation areas such as corridors, hallways and staircases. The modern, unobtrusive design, combined with a homogeneous light distribution, ensures this luminaire will blend into the architecture of most buildings. And thanks to the push-in connectors, installation of the CoreLine WL140V is fast and straightforward. This family includes Interact ready luminaires with integrated wireless communications, ready for use with Interact gateways, sensors and software.

### Product data

General Information		Flickering value (PstLM)		1
Light source replaceable	Yes	Stroboscopic effect value (SVM)	1.6	
Number of gear units	1 unit	Beam angle of light source	120 degree(s)	
Driver included	Yes	Light source color	830 warm white	
Lighting Technology	LED	Optic type	Symmetrical	
Value ladder	Performance	Luminaire light beam spread	120° x 120°	
Light Technical		Unified glare rating CEN	22	
Luminous Flux	1,275 lumen	Operating and Electrical		
Saturated Red (R9)	<50	Input Voltage	220-240 V	
Correlated Color Temperature (Nom)	3000 K	Line Frequency	50 or 60 Hz	
Luminous Efficacy (rated) (Nom)	105 lm/W	Input Frequency	50 or 60 Hz	
Color rendering index (CRI)	>80	Initial CLO power consumption	- W	

## CoreLine Wall-mounted

Average CLO power consumption	- W
Power Consumption	12 W
Inrush current	14 A
Inrush time	0.007 ms
Power Factor (Fraction)	0.9
Connection	Push-in connector 6-pole
Cable	-
Number of products on MCB of 16 A type B	32

### Temperature

Ambient temperature range	-20 to +40 °C
---------------------------	---------------

### Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

### Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover/lens finish	Opal
Overall height	85 mm
Overall diameter	390 mm

### Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK10 [20 J vandal-resistant]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years

Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.4338,0.4030) SDCM <3
Power consumption tolerance	+/-10%

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life	5 %
50000 h	
Lumen maintenance at median useful life*	-
35000 h	
Lumen maintenance at median useful life*	80
50000 h	
Lumen maintenance at median useful life*	-
75000 h	
Lumen maintenance at median useful life*	-
100000 h	

### Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	No

### Product Data

Full product code	871951452871099
Order product name	WL140V LED12S/830 PSU WH
Order code	911401847382
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	911401847382
Full product name	WL140V LED12S/830 PSU WH
EAN/UPC - Case	8719514528871



## CoreLine Wall-mounted

### Dimensional drawing

