



BR/R LED

PILA LED 50W GU10 CW 60D ND 1CT/10

Philips BR Dimmable LED Lamps with AirFlux technology provide a soft, diffused level of light and smooth dimming to reduce glare. The sleek, lightweight design is ideal for downlighting.

Product data

General Information	
Cap-Base	GU10 [GU10]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	30000X
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	60 °
Luminous Flux (Nom)	360 lm
Luminous Intensity (Nom)	430 cd
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	76.00 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	360 lm
Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Nom)	4.7 W
Lamp Current (Nom)	38 mA
Wattage Equivalent	50 W

Starting Time (Nom)	0.4 s
Warm Up Time to 60% Light (Nom)	0.4 s
Power Factor (Nom)	0.53
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	75 ℃
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Shape	PAR16 [PAR 2 inch]
Approval and Application	
Energy Efficiency Label (EEL)	F
Suitable For Accent Lighting	Yes
Energy Consumption kWh/1000 h	5 kWh
Product Data	
Full product code	871869653701501
Order product name	PILA LED 50W GU10 CW 60D ND 1CT/10
EAN/UPC - Product	8718696537015

Datasheet, 2021, August 5 data subject to change

BR/R LED

Order code	929001912331
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001912331



© 2021 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.