

# SLI035065NW\_PW\_IP44

SLI035065NW\_PW\_IP44



|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>40 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*            | <b>5500 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Colour of light           | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP44/IP20***</b>   |                    |               |

## Technical data

---

|                              |                          |
|------------------------------|--------------------------|
| Code                         | SLI035065NW_PW_IP44      |
| Power                        | 40 W                     |
| Nominal current              | 185 mA                   |
| Voltage                      | 230 V                    |
| Energy consumption           | 40 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | I                        |
| Power supply included        | +                        |
| Power factor                 | 0.9                      |
| Useful luminous flux*        | 5500 lm (360°)           |
| Luminous flux**              | 4800 lm (360°)           |
| Lamp efficacy                | 138 lm/W                 |
| Colour temperature           | 4000 K                   |
| Colour of light              | Neutral white            |
| Beam angle                   | 120 °                    |
| RA                           | >80                      |
| Uniformity of color SDCM max | 5                        |
| Dimmable                     | No                       |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 50000 h                  |
| Housing material             | Aluminum/Plastic         |
| Degree of protection (IP)    | IP44/IP20***             |
| Colour                       | White                    |
| Dimension (AxBxC)            | 595x595x32 mm            |
| For use                      | Inside                   |
| Assembly method              | On the ceiling, Recessed |
| Application                  | INT                      |
| Made in                      | PRC                      |

## Related documents

---



 Declaration of Conformity