

SYSTEM SHIFT - GRID M

WLD+40012



See
more


On track luminaire SYSTEM SHIFT - GRID M, with a power of 17 W, high light efficacy 100 lm/W. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 35° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.



| | | | |
|---------------------------|---------------|-----------------|---------------|
| Power | 17 W | Voltage | 48 V |
| Colour temperature | 3000 K | Colour of light | WW |
| Beam angle | 35 ° | UGR | <19 |
| Degree of protection (IP) | IP20 | | |


Technical data

| | |
|------------------------------|----------------|
| Code | WLD+40012 |
| Power | 17 W |
| Nominal current | 350 mA |
| Voltage | 48 V |
| Energy consumption | 17 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power factor | 1 |
| Useful luminous flux* | 1700 lm (360°) |
| Luminous flux** | 1000 lm (360°) |
| Lamp efficacy | 100 lm/W |
| Luminous intensity | 3100 cd |
| Colour temperature | 3000 K |
| Colour of light | WW |
| Beam angle | 35 ° |
| UGR | <19 |
| RA | >90 |
| Light source included | Yes |
| Producer of LED diodes | osram |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 to +40 ° |
| Lifespan | 50000 h |
| Housing material | AL+PC |
| Degree of protection (IP) | IP20 |
| Colour | Czarny |
| Dimension (AxBxC) | 303x23x42 mm |
| For use | Inside |
| Assembly method | NA SZYŃĘ |
| Application | Inside |
| Made in | PRC |




Related documents



 User manual



 Declaration of Conformity



 Photometric file



 3D model



| | | |
|---|--|--|
| <p>48V </p> <p>45 mm 303 mm 29 mm</p> <p>Die Montage erfolgt über ein einfaches Klick-System zusätzlich lässt sich die Leuchte je nach Bedarf verschieben</p> | <p>48V </p> <p>45 mm 303 mm 29 mm</p> <p>Luminaire assembly within the track on "click" and its free arrangement</p> | |
|---|--|--|

