

PRODUCT-DETAILS

6139053

AQL 02A/1/DALI/LED



General Information

| | |
|-----------------------|---|
| Extended Product Type | 6139053 |
| Product ID | 7TCA091180R0320 |
| EAN | 8713812769745 |
| Catalog Description | AQL 02A/1/DALI/LED |
| Long Description | Self-contained 1 watt maintained surface mount led luminaire, + DALI control module, series Aqualux |

Technical

| | |
|-------------------------------|--|
| Application | Industrial |
| Function | Escape route signage |
| Rated Voltage (U_r) | 220 ... 230 V |
| Input Voltage Type | AC |
| Power Supply Type | Peripheral (Individual Battery) |
| Number of Poles | 6 |
| Number of Lamps | 2 |
| Number of Lighting Heads | 1 |
| Functional Testing Capability | Safety Module for Monitoring (Central Fedded System) |
| Wiring Configuration | Wiring system: Continuous circuit/emergency circuit Type of wiring: Suitable for through wiring |
| Ballast Type | Current Controlled |

| | |
|---------------------------------|---|
| Connection Type | Screw |
| Lamp Type | LED not exchangeable |
| Light Distribution Type | Diffuser Lens Optic Panel |
| Marking Type | InsertSheet Plate |
| Mounting Type | Wall surface mounted / ceiling surface mounting |
| Type of Indicator | Single-sided |
| Cover Material | Plastic, Transparent |
| Housing Material | Plastic |
| Communication | DALI |
| Illuminance | 89 lm |
| Housing Color | Aluminium |
| Battery Chemical Composition | Nickel-Cadmium |
| Battery Type | Industrial |
| Battery Weight | 180 g |
| Number of Batteries | 4 |
| | 6350-6350 K |

Environmental

| | |
|----------------------|---------------------|
| Ambient Temperature | 0 ... 35 °C |
| Degree of Protection | IP65 |
| Protection Class | Isolated (Class II) |

Dimensions

| | |
|----------------------------------|----------------------|
| Product Net Width | 170 mm |
| Product Net Height | 75 mm |
| Product Net Depth / Length | 381 mm |
| Product Net Weight | 3.0429 lb 1.38 kg |
| Built-In Depth (t ₂) | 0 mm |

Ordering

| | |
|---------------------------------|--------------|
| Minimum Order Quantity | 1 EA |
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 1.643 kg |
| UPC | 075114353304 |

Certificates and Declarations

| | |
|-----------------------------------|------------|
| Declaration of Conformity - CE | 7TKK001175 |
|-----------------------------------|------------|

Installation

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 9AKK107992A4732 |
|--------------------------|-----------------|

9AKK107992A4857

Popular Downloads

Data Sheet, Technical
Information

9AKK107992A8959

Classifications

| | |
|---------------------------------------|--|
| ETIM 8 | EC001957 - Emergency luminaire |
| ETIM 9 | EC001957 - Emergency luminaire |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 9405409100 |
| UNSPSC | 39111709 |
| eClass | V11.0 : 27110305 |
| IDEA Granular Category Code (IGCC) | 3940 >> Emergency light unit |

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Emergency Lighting

