


PRODUCT-DETAILS

OSM1250DA4N2M230C

OSM1250DA4N2M230C MOTORIZED SWITCH FUSE



Informations générales

Extension du type de produit	OSM1250DA4N2M230C
Code de produit	1SCA118851R1001
EAN	6417019505183
Description courte	OSM1250DA4N2M230C MOTORIZED SWITCH FUSE
Description longue	Including a handle for manual operation, bolt kit with nut and washers for all terminals (100A...1250A), male connectors for control circuit and a handle and spare fuse storage clip.

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Informations environnementales	1SCC311002D0201
REACH Declaration	1SCC011021D0201
Informations RoHS	1SCC011020D0201

Commande

Quantité minimum	1 pièce
Code douanier	85365080
Pays d'origine	Finland (FI)

Popular Downloads

Fiche produit, informations techniques	1SCC311013C0201
Instructions et manuels	1SCC311029M0203

Dimensions

Produit Largeur Net	710 mm
Produit Hauteur Net	391 mm
Produit Longueur Net	356 mm
Poids net	63.5 kg

Technique

Rated Operational Current AC-21A (I_e)	(500 V) 1250 A (380 ... 415 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-22A (I_e)	(500 V) 1250 A (380 ... 415 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-23A (I_e)	(500 V) 1250 A (380 ... 415 V) 1250 A (690 V) 1000 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 560 kW (500 V) 710 kW (690 V) 1000 kW
Courant thermique conventionnel à l'air libre (I_{th})	$\Theta = 40\text{ °C}$ 1250 A
Tension assignée de tenue aux chocs (U_{imp})	12 kV
Tension assignée d'isolement (U_i)	1000 V
Tension	Circuit principal 690 V AC
Courant assigné de courte durée admissible (I_{cw})	for 1 s 40 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Motor Operational Voltage	220 ... 240 V AC
Power Loss	at Rated Operating Conditions per Pole 75 W
Degré de pollution	3
Handle Type	Handle included for manual operation
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating	04 (Left Side)

Mechanism

Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Taille de fusible	NH4a
Fuse System	DIN
Mode de fonctionnement	Motor operated and manually from the front
Normes et standards	IEC 60947-3
Type de montage	Base mounting
Nombre de pôles	4
Type de borne	Lug terminals

Environnement

Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Informations environnementales	1SCC311002D0201

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	No declaration needed
REACH Declaration	1SCC011021D0201

Emballage

Emballage Niveau 1 Unités	box 1 pièce
Emballage Niveau 1 Largeur	590 mm
Emballage Niveau 1 Longueur	790 mm
Emballage Niveau 1 Hauteur	500 mm
Emballage Niveau 1 Poids	63.5 kg
Emballage Niveau 1 EAN	6417019505183

Classifications

Code de classification d'objet	Q
Catégorie DEEE	4. Large Equipment (Any External Dimension More Than 50 cm)

Catégories

Produits basse tension → Interrupteurs → Motorized Switch Fuses

